

DIGITUS 1.25 Gbps copper SFP-module, RJ45

DN-81005

EAN 4016032389484



1.25 Gbps Copper SFP Module, RJ45 10/100/1000Base-T, up to 100m

The DIGITUS® Mini GBIC (SFP) transceiver modules offer the highest quality and reliability. The module offers a perfect opportunity for you to extend your Gigabit network switch with a free SFP Uplink Port around an additional RJ45 connection. Thanks to the hot-plug capability, you can install the module without any interruption to the network traffic or restart of the device. In addition, conformity with the MSA (Multi Source Agreement) standard provides compatibility with the current network switch manufacturers.

The plug and play extension for your network switch

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon, Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- Up to 1.25 Gbps bidirectional maximum data rate
- Compliant to IEEE 802.3z Gigabit Standard

- High quality and excellent reliability
- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant
- Hot pluggable - installation possible while in operation
- Auto MDI/MDI-X
- Connection: 1x RJ45, CAT 5
- Distance: up to 100 m
- Operating temperature: 0 °C ~ 70 °C

Attributes

- Mode: Copper
- Connector: RJ45
- Distance (km): 0.1
- DDM Support: no
- Manufacturer compatibility: Universal (MSA)
- Ethernet speed: Gigabit

Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	120	7.00	25.40	39.40	55.00	55,041.80
Packaging Unit Inside	30	1.75	7.00	20.00	30.00	4,200.00
Packaging Unit Single	1	0.06	3.20	9.30	12.00	357.12
Net single without Packaging	1	0.04	3.20	9.30	12.00	357.12

More images:

SFP Modules						
Product Number	Data Rate	Speed	Distance	Connector	Wavelength	Operating Temperature
250-0100	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0101	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0102	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0103	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0104	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0105	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0106	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0107	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0108	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0109	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0110	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0111	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0112	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0113	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0114	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0115	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0116	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0117	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0118	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0119	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0120	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0121	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0122	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0123	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0124	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0125	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0126	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0127	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0128	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0129	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0130	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0131	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0132	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0133	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0134	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0135	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0136	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0137	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0138	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0139	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0140	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0141	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0142	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0143	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0144	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0145	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0146	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0147	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0148	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C
250-0149	40 Gb/s	100 Gbps	10 km	LC	1550 nm	0 to 70 °C
250-0150	40 Gb/s	100 Gbps	10 km	LC	1310 nm	0 to 70 °C



Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com