

1

DIGITUS Assembly kit for outdoor cable with an outer diameter of up to 9 mm

DN-IND-KIT EAN 4016032429630





Assembly kit for outdoor cable, IP67 waterproof, compatible with DN-IND-C line

Assembly kit for outdoor cable, IP67,waterproof, compatible with $\ensuremath{\mathsf{DN-IND-C}}$ line

Best performance and link quality for your network. Ideal for industrial applications.

Main body & sealing nut: Nylon PA-66 high-impact UL94V-0 thermoplastic, 30% glass fiber filled

- Black gasket: Rubber
- Operating temperature range: -10 °C up to +60 °C
- Storage temperature range: -40 °C up to + 68 °C
- Humidity: 10%~90% RH

Logistics Number Weight Depth Width Height ст³ (pcs) (kg) (cm) (cm) (cm) Packaging Unit Carton 250 17.75 37.00 48.00 25.00 44,400.00 Packaging Unit Inside 100 7.10 23.00 34.00 22.00 17,204.00 1 0.07 Packaging Unit Single 9.00 3.00 4.50 121.50 Net single without Packaging 1 0.03 9.00 3.00 4.50 121.50

Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product
- · Observe the specifications of the raw cable manufacturer during installation

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com