

# DIGITUS® Mini DisplayPort Adapter Cable, mDP - HDMI type A

AK-340304-020-W  
EAN 4016032438625



**DisplayPort Adapter Cable, Type mini DP-HDMI A M/M, 2.0m, 4K@60Hz, DP1.2, HDMI 2.0, wh**

This high performance HD digital audio and video cable for example is used to connect a PC or notebook with Mini DisplayPort interface to a monitor with HDMI interface.

**Avoid the hassle of adapters, with a plug-and-play adapter cable which doesn't require external power**

- Support of HDMI 2.0 Features
- Support up to 4K/2K with 60Hz
- Support of 3D with 1080p resolution
- Support of HDCP and DPCP
- Supported transmission modes: RBR, HBR, HBR2
- Maximal bandwidth: 21,6 Gbps
- HBR-Version/transfer mode: HBR2 (5,40 Gbit/s per lane)

**Attributes**

- Assortment: DisplayPort Cables
- AWG: 30
- Color cable: white
- Color connector: white
- Connector 1: Mini DP, plug
- Connector 2: HDMI type A, plug
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.2
- Ferrite filter: none
- HDTV Standard: Ultra HD 4K
- Hoods: molded
- Interlock: none
- Packaging: Polybag
- Wire material: CU
- Length: 2 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	60	4.00	43.00	43.00	25.00	46,225.00
Packaging Unit Inside	10	0.67	40.00	34.00	10.00	13,600.00
Packaging Unit Single	1	0.07	16.00	24.00	10.00	3,840.00
Net single without Packaging	1	0.06	16.00	24.00	10.00	3,840.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)