

## **DIGITUS CAT 6 S/FTP patch cord, 5 units**

DK-1644-200-5 EAN 4016032441519





## CAT 6 S-FTP patch cord, Cu, LSZH AWG 27/7, length 20 m, 5 pieces, color grey

The DIGITUS® Category 6 Class E patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 6 specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS® Category 6 cabling. The performance is tested up to 250 MHz inclusive performance characteristics such as near end cross talk ("NEXT"). DIGITUS® patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. You can easily identify the Category 6, because of the transparent red colored connector.

## Future-oriented standards and high-end quality for your network.

- 2x RJ45 (8P8C) connectors
- · Boots with kink protection, strain relief and latch protection
- Length marking on boot
- Conductor: Copper (Cu)
- 5 pieces
- Configuration: 1:1
- Connector 1: Modular RJ45 (8/8) plug
- Connector 2: Modular RJ45 (8/8) plug
- Packaging: DIGITUS Polybag
- Category: CAT 6
- · Shielding: S-FTP, pairs in metal foil and braid shielding
- Length: 20 m
- Color: grey
- Jacket: LSOH
- Slim Version: no
  Structure: 4 x 2 AWG 27/7, twisted pair

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	12.90	36.00	36.00	22.00	28,512.00
Packaging Unit Inside	5	3.23	22.50	32.00	47.00	33,840.00
Packaging Unit Single	1	0.65	4.50	23.00	32.00	3,312.00
Net single without Packaging	1	0.61	4.50	23.00	32.00	3,312.00

## More images:









