4 Port Gigabit Ethernet Network PoE Switch, Industrial, Unmanaged, 2 SFP Uplink

DN-651106 EAN 4016032445784





Industrial Gigabit Ethernet Switch 4-ports + 2-port SFP, DIN rail, extended temp.

The DIGITUS® Industrial Gigabit Switch is designed for harsh environments, where it is exposed to moisture, temperature fluctuations, and vibrations. With a temperature range of -40°C to 85°C, the Industrial Gigabit Switch can be used under the most adverse conditions. It ensures a constant availability in highly sensitive areas such as transport, production, traffic and safety monitoring. The simple plug and play system allows the Industrial Gigabit Switch to be quickly integrated into the respective environment. With its Gigabit connectivity and SFP Uplink Ports, the Industrial Gigabit Switch is a flexible, cost-effective solution for the industrial environment.

Standard / Din Rail mounting dual purpose

- 4 x 10/100/1000Base-TX Ethernet Ports
- 2 x 1000Base-X SFP Uplink Ports
- Automatic cable detection Auto MDI / MDI-X function
- Supported standards: IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3z Gigabit Ethernet
- · Compact, robust metal housing
- Excellent short circuit protection
- · Lightning and overvoltage protection

- · Suitable for DIN rail (top-hat rail) mounting
- Redundant power supply: 12~56 V DC, redundant power supply with reverse polarity protection function
- Extended operating temperature range, -40 °C ~ +85 °C
- Removable terminal connection
- Protection class: IP40

Attributes

- Number of ports: 4
- Ethernet speed: Gigabit
- Industrial usage: yes
- Installation type: DIN rail
- Managed: no
- Number of ports (Uplink): 2
- Outdoorsuitable: no
- PoE (Power over Ethernet): no
- Protection against vanadlism: no
- · Uplink port connection: SFP
- VLAN: no

Package contents

- Industrial 4-Port Gigabit Switch with 2 x SFP uplink
- Quick start guide

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	12.00	45.00	36.00	37.00	59,940.00
Packaging Unit Inside	1	0.60	7.00	18.00	22.00	2,772.00
Packaging Unit Single	1	0.60	7.00	18.00	22.00	2,772.00
Net single without Packaging	1	0.48	7.00	18.00	22.00	2,772.00

More images:














Safety notes

- This product is intended for indoor use only.
- Read all instructions and follow all warnings and instructions on the device.
- Do not place this appliance on an unstable surface (such as a trolley, stand, table, etc.).
- Do not use this appliance near water.
- Do not place this appliance near or above a radiator.
- The housing is equipped with openings for heat dissipation and ventilation. To prevent overheating during operation, the ventilation openings
 must not be blocked or covered.
- Do not place the appliance on a soft surface (e.g. bed, sofa, blanket, etc.). This will block the ventilation.
- The appliance must not be installed in a closed environment if adequate ventilation is not guaranteed.
- Do not spray any liquids onto the appliance.
- Disconnect the mains plug before cleaning. Do not use any liquid or foam cleaners.
- Clean the appliance with a damp cloth.
- Connect the device according to the power supply on the rating plate.
- To prevent damage to the appliance, it is important that all appliances are properly earthed.
- Do not place any objects on the power cable and lay it in such a way as to avoid tripping hazards.
- Use a surge protector, a regulator or an uninterruptible power supply (UPS) to protect your system from sudden, temporary and reduced power.
- Secure the system cable and mains cable properly and ensure that no objects are pressing on the cable.
- Do not insert any objects into the appliance through the openings in the housing. There is a risk of a short circuit, which can lead to fire or electric shock.
- Do not attempt to repair the appliance yourself. Always contact an authorized customer service centre.
- If any of the following conditions occur, unplug the appliance and send it to an authorized service centre for repair
- The mains cable, power supply unit or plug for the power supply is damaged or worn;
- Liquid has penetrated the appliance;
- The device has been exposed to rain or water;
- The device has been dropped or the housing has been damaged;
- The function of the device has obviously changed;
- The appliance cannot be operated as described in the operating instructions.