

DIGITUS USB Type-C™ HDMI Multiport Adapter, 3-port

DA-70855

EAN 4016032447498



USB Type-C HDMI Multiport Adapter 4K@30Hz 1x HDMI, 1x USB-C Port (PD), 1x USB 3.0

The USB Type-C™ HDMI multiport adapter, 3-port extends your USB-C™ device with three additional ports. Use the HDMI port to connect an additional TV set or monitor to your laptop or hold a presentation with a projector. The highest possible resolution is UHD (4K/30Hz). In addition, the adapter has a USB 3.0 port to connect external USB devices. It also complies with USB-BC specification 1.2 (USB Battery Charging) and is thus suitable for charging mobile devices (max. 5V/1.5A). Moreover, it features a USB-C™ port with Power Delivery (PD) 2.0 functionality to power your laptop while using the adapter. The multiport adapter is suitable for all operating systems: Windows, Mac, Google Chrome.

Extends your USB-C™ device with three additional ports (HDMI, USB 3.0 and USB-C™)

- Connection 1: USB-C™ plug
- Connection 2: HDMI socket
- Connection 3: USB 3.0 socket
- Connection 4: USB-C™ socket
- Extends your USB-C™ device with three additional ports (HDMI, USB 3.0 and USB-C™)
- 1x HDMI (UHD, 4K/30Hz)

- 1x USB 3.0 (SuperSpeed, max. 5 Gbps) - supports BC 1.2 for charging mobile devices (5V/1.5A)
- 1x USB-C™ (PD 2.0, max. 60W)
- Supports Ultra HD (4K/30Hz)
- USB-C™ version: USB 3.1 (Gen. 1)
- USB-BC (USB Battery Charging) 1.2
- Corresponds to the VESA DisplayPort Alternate Mode
- Chipset: AG6310, LDR6023SD
- Cable length: 15.0 cm
- Color: Black
- Dimensions: L 20.0 x W 7.7 x H 1.7 cm
- Weight: 40 g
- Not all USB-C™ ports support all functions of USB Type-C™ standards. Make sure that the USB-C™ port of your laptop supports the DisplayPort Alternate Mode (DP Alt-mode).
- The video output capability depends on the graphics card of your laptop and the connected monitor. Some screens also have a limited resolution.

Attributes

- USB-C Products: yes

Package contents

- USB Type-C™ HDMI Multiport Adapter, 3-port
- QIG (quick installation guide)

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	100	7.20	50.40	21.30	46.80	50,240.70
Packaging Unit Inside	1	0.07	19.00	8.60	2.20	359.48
Packaging Unit Single	1	0.07	19.00	8.60	2.20	359.48
Net single without Packaging	1	0.03	19.00	8.60	2.20	359.48

More images:**Safety notes**

- Overloading can lead to overheating and damage to the appliance or the connected peripherals.
- If necessary, use an external power supply to ensure stable performance.
- If devices such as external hard disks or printers that require a high power consumption are connected, the device should be used with an external power supply. Otherwise, the device could be overloaded or functional problems could occur.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com