

DIGITUS USB-C 3.2 Gen 1 to HDMI Graphic Adapter

DA-70852

EAN 4016032447528



USB-C 3.2 Gen 1 to HDMI Graphic Adapter 1x HDMI, 4K/60Hz, Black

Our USB-C 3.2 Gen 1 hub offers maximum flexibility and efficiency. With HDMI support for 4K/60Hz and dual display function (screen extension or mirroring), it enables seamless integration into your working environment. Thanks to USB plug-and-play, the monitor can be added or removed without a system restart. Up to two graphics adapters can be used simultaneously. The hub also offers automatic resume from sleep mode and backwards compatibility with older HDTVs and projectors. Ideal for modern and flexible working environments.

Extend your display options to other devices with the USB-C 3.2 Gen 1 to HDMI Graphic Adapter

- Connections:
- 1x USB-C 3.2 Gen 1 - Host connection
- 1x HDMI - Max. Resolution 4K/60Hz
- Dimensions: 4.5 x 4.5 x 1.5 cm

- Weight: 32 g
- Product color: Black
- Cable color: Black
- Cable length: 15 cm
- Housing: Plastic
- Power consumption: Max. 900 mA
- Chipset information: CS5265
- Operating system compatibility: Windows 7 or higher, macOS 10.8 or higher, iOS (iPhone 15 or higher), iPadOS, ChromeOS, Android, Linux
- Supports dual display (expand screen / mirror screen)

Attributes

- USB-C Products: yes

Package contents

- 1x USB-C 3.2 Gen 1 to HDMI Graphic Adapter
- 1x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	125	8.38	35.00	35.00	46.00	56,350.00
Packaging Unit Inside	1	0.07	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.07	2.00	8.50	14.00	238.00
Net single without Packaging	1	-0.29	2.00	8.50	14.00	238.00

More images:



Safety notes

- Overloading can lead to overheating and damage to the appliance or the connected peripherals.
- If necessary, use an external power supply to ensure stable performance.
- If devices such as external hard disks or printers that require a high power consumption are connected, the device should be used with an external power supply. Otherwise, the device could be overloaded or functional problems could occur.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schöffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com