

# DIGITUS 17" LCD KVM Console, 16-Port VGA, german **Keyboard**

DS-72210-3GE EAN 4016032449317





## Modularized 43,2cm (17") TFT console with 16 port KVM, German keyboard, RAL 9005 black

Due to its modular design, the DIGITUS® 17" TFT console offers a multitude of individual configuration possibilities, so that it can be adjusted to the area in which the console is being used. As a result, the console is economical and can be upgraded and/or converted at any time with further modules. Due to the flexible configuration, a high level of future security of the console is thus guaranteed. The modular console consists of a 17" monitor, 16-port KVM switch, keyboard and the touchpad.

## Highest degree of flexibility during the administration of the server farm

- TFT monitor 43.2 cm (17"), with anti-reflective, break-proof protective glass screen
- Resolution: 1280x1024 at 60 Hz
- Console creates up to 85% more space
- Contrast ratio: 1000:1
- Supports: 16.7 M colors
- Including 16-port KVM switch
- Including german keyboard
- Mouse touch-board with two function keys

- The console can be completely extracted from the server cabinet, and the TFT screen can be tilted through 120 degrees
- Gross weight: 19,15 kg
- The consoles have safety locking in order to prevent damage
- Space-saving housing (1U), black (RAL 9005)
- 16 x Combo KVM cable

## **Attributes**

- Cascading possible: yes
- Interface: VGA
- Keyboard Layout: DE
- Number of ports: 16
- Screen size: 17 inch

## **Package contents**

- Modular 17" console
- 16-port KVM switch
- Keyboard
- Quick start guide
- Power adapter
- Mounting material 16 x Combo KVM cable

| Logistics                    |                 |                |               |               |                |            |
|------------------------------|-----------------|----------------|---------------|---------------|----------------|------------|
|                              | Number<br>(pcs) | Weight<br>(kg) | Depth<br>(cm) | Width<br>(cm) | Height<br>(cm) | cm³        |
| Packaging Unit Carton        | 1               | 23.36          | 81.00         | 70.50         | 19.50          | 111,355.00 |
| Packaging Unit Inside        | 1               | 23.36          | 81.00         | 70.50         | 19.50          | 111,355.00 |
| Packaging Unit Single        | 1               | 23.36          | 81.00         | 70.50         | 19.50          | 111,355.00 |
| Net single without Packaging | 1               | 19.56          | 81.00         | 70.50         | 19.50          | 111,355.00 |



#### More images:






















# Safety notes

- This product is intended for indoor use only.
- · Read all instructions.
- Follow all warnings and instructions on the device.
- Do not place this appliance on an unstable surface (such as a trolley, stand, table, etc.).
- If this appliance falls, it can cause serious damage.
- Do not use this appliance near water.
- Do not place this appliance near or above a radiator.
- The housing is equipped with openings for heat dissipation and ventilation. To prevent overheating during operation, the ventilation openings
  must not be blocked or covered.
- Do not place the appliance on a soft surface (e.g. bed, sofa, blanket, etc.). This will block the ventilation.
- · The appliance must not be installed in a closed environment if adequate ventilation is not guaranteed.
- Do not spray any liquids onto the appliance.
- Disconnect the mains plug before cleaning. Do not use any liquid or foam cleaners.
- Clean the appliance with a damp cloth.
- Connect the device according to the power supply on the rating plate.
- This device is designed for the IT distribution system with 100 V 230 V voltage.
- To prevent damage to the appliance, it is important that all appliances are properly earthed.
- Do not place any objects on the power cable and lay it in such a way as to avoid tripping hazards.
- If an extension cable is used for the appliance, make sure that the total capacity of all products using the cable does not exceed the current load.
- Ensure that the total current of all products connected to the socket does not exceed 15 A.
- Use a surge protector, a regulator or an uninterruptible power supply (UPS) to protect your system from sudden, temporary and reduced power.
- Secure the system cable and mains cable properly and ensure that no objects are pressing on the cable.



- Do not insert any objects into the appliance through the openings in the housing. There is a risk of a short circuit, which can lead to fire or electric
- Do not attempt to repair the appliance yourself. Always contact an authorized customer service centre.
- If any of the following conditions occur, unplug the appliance and send it to an authorized service centre for repair
- The mains cable or plug is damaged or worn; Liquid has penetrated the appliance;
- The device has been exposed to rain or water;
- The device has been dropped or the housing has been damaged;
- The function of the device has obviously changed;
- The appliance cannot be operated as described in the operating instructions.

## EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com