

DIGITUS 19" LCD KVM Console, 8-Port VGA, swiss Keyboard

DS-72211-2CH EAN 4016032449911





Due to its modular design, the DIGITUS® 19" TFT console offers a multitude of individual configuration possibilities, so that it can be adjusted to the area in which the console is being used. As a result, the console is economical and can be upgraded and/or converted at any time with further modules. Due to the flexible configuration, a high level of future security of the console is thus guaranteed. The modular console consists of a 19" monitor, 8-port KVM switch, keyboard and the touchpad.

Highest degree of flexibility during the administration of the server farm

- TFT monitor 48.3 cm (19"), with anti-reflective, break-proof protective glass screen
- Resolution: 1366x768 at 60 Hz
- Console creates up to 85% more space
- Contrast ratio: 1000:1
 Supports: 16.7 M colo
- · Supports: 16.7 M colors
- Including 8-port KVM switch
- Including swiss keyboard
- · Mouse touch-board with two function keys

Net single without Packaging



- The console can be completely extracted from the server cabinet, and the TFT screen can be tilted through 120 degrees
- Gross weight: 19,15 kg
- · The consoles have safety locking in order to prevent damage
 - Space-saving housing (1U), black (RAL 9005)
- 8 x Combo KVM cable

Attributes

- Cascading possible: yes
- Interface: VGA
- · Keyboard Layout: CH
- Number of ports: 8
- Screen size: 19 inch

Package contents

- Modular 19" console
- 8-port KVM switch
- Keyboard
- Quick start guide
- Power adapter
- Mounting material8 x Combo KVM cable

70.50

19.50

111,355.00

Logistics Width Number Weight Depth Height cm³ (pcs) (cm) (cm) (cm) (kg) Packaging Unit Carton 1 23.36 81.00 70.50 19.50 111,355.00 Packaging Unit Inside 1 23.36 81.00 70.50 19.50 111,355.00 23.36 81.00 70.50 19.50 111,355.00 Packaging Unit Single 1

22.66

81.00




More images:

















Safety notes

- This product is intended for indoor use only.
- Read all instructions.
- · Follow all warnings and instructions on the device.
- Do not place this appliance on an unstable surface (such as a trolley, stand, table, etc.).
- If this appliance falls, it can cause serious damage.
- Do not use this appliance near water.
- Do not place this appliance near or above a radiator.
- The housing is equipped with openings for heat dissipation and ventilation. To prevent overheating during operation, the ventilation openings
 must not be blocked or covered.
- Do not place the appliance on a soft surface (e.g. bed, sofa, blanket, etc.). This will block the ventilation.
- · The appliance must not be installed in a closed environment if adequate ventilation is not guaranteed.
- Do not spray any liquids onto the appliance.
- Disconnect the mains plug before cleaning. Do not use any liquid or foam cleaners.
- Clean the appliance with a damp cloth.
- Connect the device according to the power supply on the rating plate.
- This device is designed for the IT distribution system with 100 V 230 V voltage.
- To prevent damage to the appliance, it is important that all appliances are properly earthed.
- Do not place any objects on the power cable and lay it in such a way as to avoid tripping hazards.
- If an extension cable is used for the appliance, make sure that the total capacity of all products using the cable does not exceed the current load.
- Ensure that the total current of all products connected to the socket does not exceed 15 A.
- Use a surge protector, a regulator or an uninterruptible power supply (UPS) to protect your system from sudden, temporary and reduced power.
- Secure the system cable and mains cable properly and ensure that no objects are pressing on the cable.
- Do not insert any objects into the appliance through the openings in the housing. There is a risk of a short circuit, which can lead to fire or electric shock.
- Do not attempt to repair the appliance yourself. Always contact an authorized customer service centre.
- If any of the following conditions occur, unplug the appliance and send it to an authorized service centre for repair
- The mains cable or plug is damaged or worn;
- Liquid has penetrated the appliance;
- The device has been exposed to rain or water;
- · The device has been dropped or the housing has been damaged;
- The function of the device has obviously changed;
- The appliance cannot be operated as described in the operating instructions.



EU responsible person

 $\label{thm:equired} \mbox{EU based economic operator ensuring the product complies with the required regulations.}$ ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com