

DIGITUS® USB-C 3.2 Gen2 adapter / converter cable, USB-C - HDMI

AK-300330-020-S
EAN 4016032451334



USB Type-C adapter cable, Type-C to HDMI A M/M, 2.0m, 4K/60Hz, 18GB, bl, gold

The USB Type-C 4K HDMI adapter/converter cable enables the direct connection of a TV, monitor or projector to a USB-C device. The adapter/converter cable is a must-have accessory, whether you are connecting your notebook to a TV at home or using an HDMI projector for presentations at work.

Connect your USB-C device directly to a monitor, TV or projector - you don't need an additional adapter.

- Your USB-C equipped device must support video mode (DP Alt Mode) to be compatible with this adapter / converter cable.
- The video output capability depends on the graphics card of your notebook and the connected monitor. Some monitors also limit the available resolution.

- Supports up to 4K/2K with 60Hz
- Support for digital audio transmission in stereo
- Data transfer rate up to 18 Gbit/s
- Complies with the DisplayPort HBR2 standard (5.4 Gbit/s per lane)

Attributes

- AWG: 26
- Color cable: black
- Connector 1: USB C, plug
- Connector 2: HDMI type A, plug
- Connector surface: nickel-plated
- Ferrite filter: 2 x ferrite beads
- USB compliance: USB 2.0
- Length: 2 m
- Shielding: Double shielding

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm ³ |
| Packaging Unit Carton | 40 | 5.80 | 35.00 | 26.00 | 24.00 | 21,840.00 |
| Packaging Unit Inside | 10 | 1.45 | 28.00 | 11.00 | 21.00 | 6,468.00 |
| Packaging Unit Single | 1 | 0.15 | 17.00 | 3.00 | 12.00 | 612.00 |
| Net single without Packaging | 1 | 0.14 | 17.00 | 3.00 | 12.00 | 612.00 |

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com