

DIGITUS Fiber Optic Splice Box Front Panel, quick lock, 24x LC DX, SC SX, E2000 SX

DN-96207-BL-QL
EAN 4016032458425



FO front panel, 1U, quick lock, 24x LC DX, SC SX E2000 SX, vertically, color black (RAL 9005)

The DIGITUS® front panel was designed for the basic housing DN-96200-BL-QL. You can easily install the front panel with the fixing material included in the packing of the basic housing. The new quick lock system makes the operation easier and faster than ever before.

Future-oriented standards and high-end quality for your network.

- for vertical mounting of respective couplers

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	60	12.00	46.00	16.00	16.00	11,776.00
Packaging Unit Inside	1	0.20	2.00	5.00	43.00	430.00
Packaging Unit Single	1	0.20	2.00	5.00	43.00	430.00
Net single without Packaging	1	0.15	2.00	5.00	43.00	430.00

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com