

# DIGITUS® USB-C - Lightning data/charging cable, MFI certified, 1m

DB-600109-010-W  
EAN 4016032469957



### USB charger/data cable, Lightning - USB-C M/M, 1.0m, PVC, MFI, wh, 20V/3A 60W

Connect your iPhone, iPad or iPod with Lightning connector to your USB-C-capable MacBook, notebook or PC for synchronizing or charging. This cable can also be used with a USB-C charger. The charging adapters with 29, 30, 61 and 87 watts of power are compatible. Numerous iPhone and iPad Pro models also support the Power Delivery 2.0 fast charging function. The maximum supported charging power of the MFI-certified cable is 18 W.

#### Fast charging & data transfer - 100% compatible

- Supports Power Delivery (PD 2.0) fast charging function for compatible devices\*
- Can be used with USB-C power adapter 29 W, 30 W, 61 W and 87 W
- Supports PD 2.0 Fast Charging
- Bending service life: 30,000 bends / high tensile strength
- Max. supported charging power: 20V/3A 60W
- Data rate: 480 Mbit/s
- Chipset: C94
- Material: Plastic
- Color: White

- Length: 1m
- \*Compatibility list: Supports PD 2.0 Fast Charge for iPhone 8, iPhone 8 plus, iPhone X,iPhone XR,iPhone XS Max, iPhone 11, iPhone 11 pro, iPhone 11 pro max, iPhone Pro 10.5-inch, iPad Pro 12.9-inch(2nd Generation), iPad Pro 12.9-inch(1st Generation), iPad mini(5th Generation), iPad Air(3rd Generation) + compatible models

#### Attributes

- AWG: 24
- Color cable: white
- Connector 1: Apple Lightning 8-pin, plug
- Connector 2: USB C, plug
- Connector surface: nickel-plated
- Hoods: molded
- Wire material: CU
- Length: 1 m
- Shielding: Double shielding
- USB-C Products: yes

#### Package contents

- Data/charging cable, Lightning-USB-C, 1m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	120	6.50	50.00	38.00	26.00	49,400.00
Packaging Unit Inside	10	0.54	25.00	13.00	12.00	3,900.00
Packaging Unit Single	1	0.05	2.50	9.00	11.00	247.50
Net single without Packaging	1	0.04	2.50	9.00	11.00	247.50

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)