Variable Notebook Stand with integrated USB-C™ Hub, 5 Port

DA-90424
EAN 4016032475293



Notebook Riser with 5 Port USB 3.0 Hub PD Charging, silver

The adjustable notebook stand from DIGITUS® combines ergonomic design and connectivity in one convenient unit. You can easily adjust the angle of inclination to your height in 5 levels. Your notebook can be connected via the USB-C™ port, allowing you to access all USB interfaces of the hub. 4 fully-functional USB A ports (USB 3.2 Gen1) and a USB-C™ power with Power Delivery are available. An optional USB-C™ power adapter, for example, delivers up to 100 W of charging power (Power Delivery) for a connected notebook and the USB-A ports (85 W / 15 W). Use the advantages of ergonomic design and connectivity in a single unit with the DIGITUS® notebook stand with integrated USB hub.

Flexibly adjustable, Mobile Notebook Stand with integrated USB Hub incl. USB-C™ Power Delivery - Foldable

- 1 x USB-C™ connection: USB 3.2 Gen 1, SuperSpeed, 5 Gbps max.
- 1 x USB-C™ connection: Power Delivery 3.0 (85 W max. / Fast Role Swap)
- 3 x USB A connections: USB 3.2 Gen1, SuperSpeed, 5 Gbps (5 V / 0.9 A)
- 1 x USB A connection: USB 3.2 Gen1, SuperSpeed, 5 Gbps (5 V / 1.5 A)
- Charging power of all USB A connections: 15 W max.
- Compatible with notebooks, tablets from many manufacturers
- Suitable for notebooks with a screen diagonal of 10" - 17"
- Slim frame design for optimal notebook cooling
- Adjustable angle of inclination: 15° - 36°
- Operating temperature: 0 ° to +45 °C
- Operating humidity: 10% to 90% RH (non-condensing)
- Storage temperature: 0 °C to 70 °C
- Storage humidity: 10% to 90% RH (non-condensing)
- Frame material: Aluminum
- Dimensions: W 25.2 x D 18.5 x H 6 cm
- Weight: 300 g
- Manufacturer's notice:
- An optional power adapter is required in order to use the charging function via Power Delivery.

Attributes

- Style: Notebook Riser




Package contents



- 1 x Variable Notebook Stand with integrated USB-C™ Hub, 5-Port
- 1 x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	40	14.60	29.00	37.00	34.00	36,482.00
Packaging Unit Inside	10	3.65	8.50	27.00	32.00	7,344.00
Packaging Unit Single	1	0.37	27.00	7.50	2.50	506.25
Net single without Packaging	1	0.34	27.00	7.50	2.50	506.25


More images:





Safety notes

- Please read the entire manual before starting assembly and installation. Please contact your local dealer if you have any questions about the instructions or warnings.
- CAUTION: Use with products that exceed the permitted weight may result in damage or possible injury.
- Brackets should be fitted in accordance with the installation instructions. Incorrect installation can result in damage or injury.
- Use safety equipment and suitable tools. The product should only be installed by specialists.
- This product can be installed on timber-framed, solid concrete or stone walls.
- The load-bearing surfaces should be able to safely withstand the entire weight of appliances and all additional components.
- Only use the installation screws supplied and DO NOT TIGHTEN the screws TOO TIGHT.
- This product contains small parts that can cause a choking hazard if swallowed. Keep these parts away from children.
- Only use this product indoors. Using the product outdoors can lead to injuries and damage.
- IMPORTANT: Before installation, please check all components received against the components list. If parts are damaged or missing, ask your local dealer for replacement parts.
- MAINTENANCE: Check the bracket regularly for safety and stability (preferably every three months).