

DIGITUS 2 Port-Gigabit-Ethernet-PoE-Switch, Industrie, unverwaltet, 1 SFP-Uplink

DN-652120

EAN 4016032482925



Industrial Media Converter 10/100/1000Base-TX (PoE) to 1000Base-FX

Industrial PoE Ethernet switch with 2-Port 10/100/1000Mbps RJ45(PoE) +1 Port 1000Mbps SFP, the Product meet CE, RoHS standards. DN-652120 switch has the operating temperature of -40~80, has the super firmness can adapt to all kinds of harsh environment, can also be conveniently placed in the compact space of the control box. The installation characteristics of the guide rail, wide temperature operation, IP40 protection class housing and LED indicator light make the DN-652120 a plug and play industrial grade device, providing a reliable and convenient solution for users to network their Ethernet devices.

Industrial PoE Ethernet switch with 2-Port 10/100/1000Mbps RJ45(PoE) +1 Port 1000Mbps SFP

- Ensure reliable data transmission
- Support full duplex or half duplex mode, with automatic negotiation capability
- Network port support automatic cross identification
- Internal storage and forwarding mechanism, support a variety of protocols
- In line with industrial operating standards, the average trouble-free work in more than 300,000 hours
- Working power supply: DC 48-57V to provide reverse protection
- Standard: IEEE802.310BASE-TIEEE802.3i 10Base-T;IEEE802.3u;100Base-TX/FX;IEEE802.3ab1000Base-T;IEEE802.3z1000Base-X;IEEE802.3x; IEEE802.3af, IEEE802.3at

- Work environment: -40~80 °C
- Storage: -40~80 °C
- Bandwidth: 14Gbps
- Packet Buffer Memory:1.2Mbit
- Packet Forwarding Rate:10.5Mpps
- MAC Address Table: 2K
- Power supply: input voltage: DC48-57V
- two-way power redundancy backup
- Support reverse connection protection
- IP40 aluminum housing
- DIN rail install
- Natural cooling, no fan
- Weight: 0.42Kgs
- Measurement: 118 x 92.4 x 40 mm
- Total PoE Power budget (W): 60W
- Connector 1: RJ45
- Connector 2: SFP
- Connector: RJ45
- DDM Support: no
- Industrial usage: yes
- PoE injector: yes
- PoE injector: yes

Package contents

- industrial Switch 2xRJ45 1xSFP
- User Manual

Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	24	12.70	39.00	46.50	22.50	40,803.80
Packaging Unit Inside	1	0.53	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.53	13.50	16.50	5.40	1,202.85
Net single without Packaging	1	0.47	13.50	16.50	5.40	1,202.85

More images:

