

# DIGITUS®

DK-D3902-1-SC-W  
EAN 4016032485421



FO, Breakout SC/SC SM 2E9/125µ, G.657A1, indoor LSOH, B2ca, dedicated for FTTH, white jacket, 1KM

**Attributes**

- Application: indoor
- Cable jacket: LSOH

- Color cable: white
- Fiber class: OS2
- Fiber diameter: 9/125µ
- Mode: Singlemode
- Number of fibers: 2

**Logistics**

|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³  |
|------------------------------|--------------|-------------|------------|------------|-------------|------|
| Packaging Unit Carton        | 1            | 0.00        | 0.00       | 0.00       | 0.00        | 0.00 |
| Packaging Unit Inside        | 1            | 0.00        | 0.00       | 0.00       | 0.00        | 0.00 |
| Packaging Unit Single        | 1            | 0.00        | 0.00       | 0.00       | 0.00        | 0.00 |
| Net single without Packaging | 1            | 0.00        | 0.00       | 0.00       | 0.00        | 0.00 |

**More images:**



**Safety notes**

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems),

- can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
  - When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
  - When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
  - Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
  - To protect cables from physical damage, they should be laid in special ducts or with protective materials
  - Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
  - Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
  - Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)