

1

# DIGITUS

DK-B3924-U-SC-1 EAN 4016032495505





FO universal DIGITUS 24 fibers central loose tube SM 9/125 G652D B2ca LSOH,1500N,bl,A/I-DQ(ZN)BH 4km

## Attributes

- Application: universal
- Cable jacket: LSOH

- Cable type: U-DQ (ZN) BH X E 9/125μm
- Color cable: black
- Fiber class: OS2
- Fiber diameter: 9/125µ
- Mode: Singlemode
- Number of fibers: 24

| Logistics                    |                 |                |               |               |                |      |
|------------------------------|-----------------|----------------|---------------|---------------|----------------|------|
|                              | Number<br>(pcs) | Weight<br>(kg) | Depth<br>(cm) | Width<br>(cm) | Height<br>(cm) | cm³  |
| Packaging Unit Carton        | 1               | 0.00           | 0.00          | 0.00          | 0.00           | 0.00 |
| Packaging Unit Inside        | 1               | 0.00           | 0.00          | 0.00          | 0.00           | 0.00 |
| Packaging Unit Single        | 1               | 0.00           | 0.00          | 0.00          | 0.00           | 0.00 |
| Net single without Packaging | 1               | 0.00           | 0.00          | 0.00          | 0.00           | 0.00 |

#### More images:



### Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect
  against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.

- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

# EU responsible person

EU based economic operator ensuring the product complies with the required regulations. ASSMANN Electronic GmbH Auf dem Schüffel 3

Lüdenscheid, Germany https://www.assmann.com info@assmann.com