

# DIGITUS® CAT 6 U/UTP outdoor patch cable, PE, 10 pieces

DK-1617-100-OD-10  
EAN 4016032508564



## CAT 6 U-UTP outdoor patch cord, Cu, PE, 10 pcs. AWG 26/7, length 10 m, black sheath color

The DIGITUS® Category 6 Class E patch cables are manufactured and tested according to the ISO/IEC 11801 and DIN EN 50173 CAT 6 standard. They guarantee that the cable installation complies with the ISO & EN Channel specification and offer excellent performance in DIGITUS® CAT 6 cabling. The performance has been tested up to 250 MHz, including performance characteristics such as near-end crosstalk ("NEXT"). The DIGITUS® patch cables have been specially developed to fully meet all requirements in the various application areas. Each cable is equipped with a molded anti-kink grommet with strain relief. The grommet also has a latching lever protection, which prevents the cable from snagging and the latching lever from breaking off the plug. With the UV-resistant PE outer sheath, this outdoor patch cable enables safe installation in areas with strong temperature fluctuations and which are exposed to the sun.

**Outstanding performance and connection quality for your network with UV resistance.**

- 2x RJ45 plug (8P8C)
- Hoods with bend protection, strain relief and latching lever protection
- Length designation on the hoods
- Inner conductor: Copper (Cu)
- UV resistant, acid, alkali and corrosion resistant
- Operating temperature range: -20 °C up to +60 °C
- 10 pieces



### Attributes

- Configuration: 1:1
- Category: CAT 6
- Shielding: U-UTP, unshielded
- Length: 10 m
- Color: black
- Jacket: PE
- Slim Version: no
- Structure: 4 x 2 AWG 26/7, twisted pair
- Flat Version: no

## Logistics

|                                 | Number<br>(pcs) | Weight<br>(kg) | Depth<br>(cm) | Width<br>(cm) | Height<br>(cm) | cm³       |
|---------------------------------|-----------------|----------------|---------------|---------------|----------------|-----------|
| Packaging Unit Carton           | 5               | 12.00          | 36.00         | 36.00         | 27.00          | 34,992.00 |
| Packaging Unit Inside           | 1               | 2.40           | 14.00         | 30.00         | 36.00          | 15,120.00 |
| Packaging Unit Single           | 1               | 2.40           | 2.80          | 19.00         | 27.00          | 1,436.40  |
| Net single without<br>Packaging | 1               | 2.37           | 2.80          | 19.00         | 27.00          | 1,436.40  |

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)