

1

DIGITUS Wall-mounted network cabinet, 19" 6U, 550x350 mm, solid door, gray, one-piece, assembled, 30kg

CL-19 06U-MD EAN 5907772594926



Attributes

- Cabinet type: Wall mounting cabinet
- Color: light grey, RAL 7035
- Front door: Steel door, closed, single opening
- Load capacity: 30 kg

- Units: 6
- Width: 550 mm IP protection class: IP20
- Mounted: yes

Safety notes

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be laid neatly and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- . Avoid moisture or wetness while observing the respective IP protection class.
- . Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com