

DIGITUS® Installation cable coaxial DIGITUS RG-6, 75 Ohm, shielded (2x foil + 77% braid), Eca, PVC, 500m, white, spool

DK-RG6-5

EAN 5907772595992



The DIGITUS® RG6 75Ω coaxial cable is designed for the transmission of high-frequency signals, operating in the range from 5 MHz to 2400 MHz. It features a shield with a minimum braid coverage of 77%, in accordance with the requirements of the Regulation of the Minister of Transport, Construction, and Maritime Economy dated November 6, 2012. It provides a high level of shielding, Class A, according to PN-EN 50117-2-4. This cable is used in terrestrial, cable, and satellite television installations,

intended for indoor use.

Attributes

- CPR: Eca
- Length: 500 m
- Color: white
- Jacket: PVC

Safety notes

- Data cables must not be bent, stretched or twisted excessively. Sharp bends can damage the cable sheath and lead to failures or short circuits.
- Installation only by trained specialists.
- For indoor cables (LSZH jacket): Suitable only for installation in dry indoor environments.
- The data cable must not be in direct contact with other electrical cables or high-voltage sources in order to avoid electromagnetic interference.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com