

DIGITUS Power strip Monitoring and switching 1U, IEC320 C20 power inlet 16A/250V, 8x C13 outlets, 16A.

DN-DP-H-1-8C13
EAN 5907772596845



Power strip IPDU H enables switching on/off of outlets and power measurement via TCP/IP. The front panel is equipped with 8 IEC320 C13 outlets. Power ports are individually switchable through a network interface, SNMP, or directly using the button on the control panel. Integration with an additional device (DN-S-BOX) allows the connection of dedicated sensors to monitor: ambient temperature/humidity, door opening/closing, and detect the presence of water or smoke.

Attributes

- Current: 16 A
- Input Plug: IEC 60320 C20 inlet
- Installation: Rack 1U
- Metering: Outlet Metering
- Outlets: IEC 60320 C13
- Phase: 1ph
- Power: 3,6 kVA
- Volts: 230 V
- Inch form factor (IEC 60297): 482.6 mm (19")

More images:



Safety notes

- This product is not intended for unsupervised use by children or persons under their care!
- Prevent higher humidity or temperatures than those specified in the data sheet - Avoid moisture, dust or vapors, solvents, flammable gases.
- Multiple sockets are not designed for permanent use with heavy loads!
- Multiple sockets must not be cascaded (avoid stringing together several multiple sockets).
- The maximum connected load must not be exceeded.
- Defective multiple sockets must be taken out of service immediately and disposed of in an environmentally friendly manner.
- In the event of a fault, take the product out of operation and contact a qualified electrician.
- Do not open the product.
- Disconnect the product from the power supply before cleaning. Do not use any aggressive or abrasive cleaning agents for cleaning.
- The ingress of liquids can lead to a short circuit.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH

Auf dem Schüffel 3

Lüdenscheid, Germany

<https://www.assmann.com>

info@assmann.com