

DIGITUS Power strip SMART PDU 0U, IEC 60309 32A/400V input plug, 18x IEC320 C13 outlets (10A/250V), 6x IEC320 C19 outlets (16A/250V), 32A

DN-IP2-V5-18C13-6C19
EAN 5907772596876



Power strip three-phase SMART PDU, 32A, allows remote monitoring and management of the power distribution system via TCP/IP network. The front panel is equipped with 18 IEC320 C13 outlets and 6 IEC320 C19 outlets. The strip features a color display. Built-in environmental ports enable monitoring of ambient temperature and humidity, door status (open/closed), and the presence of smoke and water through dedicated sensors. It also supports cascading connection of up to 4 additional power strips.

Attributes

- Current: 32 A
- Input Plug: IEC 60309 32A 3ph/N/PE 6h
- Installation: Rack 0U
- Metering: PDU Metering
- Outlets: IEC 60320 C13, IEC 60320 C19
- Phase: 3ph
- Power: 22 kVA
- Volts: 230 V

More images:



Safety notes

- This product is not intended for unsupervised use by children or persons under their care!
- Prevent higher humidity or temperatures than those specified in the data sheet - Avoid moisture, dust or vapors, solvents, flammable gases.
- Multiple sockets are not designed for permanent use with heavy loads!
- Multiple sockets must not be cascaded (avoid stringing together several multiple sockets).
- Defective multiple sockets must be taken out of service immediately and disposed of in an environmentally friendly manner.
- In the event of a fault, take the product out of operation and contact a qualified electrician.
- Do not open the product.
- Disconnect the product from the power supply before cleaning. Do not use any aggressive or abrasive cleaning agents for cleaning.
- The ingress of liquids can lead to a short circuit.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH

Auf dem Schüffel 3

Lüdenscheid, Germany

<https://www.assmann.com>

info@assmann.com