

DIGITUS® SMART PDU 1U power distribution unit, IEC 320 C20 power inlet 16A/250V, outlets: 12 × C13, 16A

DN-DP-H1-12C13

EAN 5907772596944



The IPDU H power distribution unit enables switching outlets on/off and measuring electrical energy consumption via a TCP/IP network. The front panel is equipped with 12 IEC 320 C13 outlets. The power outlets are individually switchable via the network interface, SNMP, or a button located directly on the management panel. Cooperation with an additional device (DN-S-BOX), which allows connection of dedicated sensors, enables monitoring of ambient temperature and humidity, door opening/closing, as well as detection of water or smoke presence

Attributes

- Current: 16 A
- Installation: Rack 1U
- Metering: Outlet Metering
- Outlets: IEC 60320 C13
- Phase: 1ph
- Power: 3,6 kVA
- Volts: 230 V
- Inch form factor (IEC 60297): 482.6 mm (19")

More images:



Safety notes

- This product is not intended for unsupervised use by children or persons under their care!

- Prevent higher humidity or temperatures than those specified in the data sheet - Avoid moisture, dust or vapors, solvents, flammable gases.
- Multiple sockets are not designed for permanent use with heavy loads!
- Multiple sockets must not be cascaded (avoid stringing together several multiple sockets).
- The maximum connected load must not be exceeded.
- Defective multiple sockets must be taken out of service immediately and disposed of in an environmentally friendly manner.
- In the event of a fault, take the product out of operation and contact a qualified electrician.
- Do not open the product.
- Disconnect the product from the power supply before cleaning. Do not use any aggressive or abrasive cleaning agents for cleaning.
- The ingress of liquids can lead to a short circuit.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com