

# **DIGITUS USB connection cable**

AK-300102-030-S EAN 4016032284796





### USB connection cable, type A - B M/M, 3.0m, USB 2.0 suitable, bl

For connection of external USB devices (with B socket, e. g. external HDD enclosure, scanner or printer) to the USB Host (e. g. PC, Notebook or USB Hub). Datatransferrate up to 480 Mbps (High-Speed).

Allows a reliable and fast connection of external USB devices to the PC.

## Attributes


- Assortment: USB Cables
- · Color cable: black
- · Color connector: black
- Connector 1: USB A, plug
- Connector 2: USB B, plugConnector surface: nickel-plated
- Hoods: molded
- USB compliance: USB 2.0
- Length: 3 m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	230	14.80	45.00	32.00	25.00	36,000.00
Packaging Unit Inside	10	0.64	32.00	25.00	3.00	2,400.00
Packaging Unit Single	1	0.06	0.50	25.00	14.00	175.00
Net single without Packaging	1	0.06	14.00	1.00	10.00	0.00

## More images:











#### Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- · Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum
  operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

## EU responsible person

 $\ensuremath{\mathsf{EU}}$  based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com