

DIGITUS DisplayPort Connection Cable

AK-340102-020-W
EAN 4016032289333



DisplayPort connection cable, mini DP - DP M/M, 2.0m, w/interlock, DP 1.1a conform, wh

This high performance HD digital audio and video cable suits for connection of a MacBook, MacBook Air, MacBook Pro, iMac, Mac mini and Mac Pro to a Monitor, Beamer, LCD/TFT Monitor with DP interface, for example.

Ideal to connect mobile devices with displays

- Support 1080p with 30Hz
- Max. supported Video Resolution: 1920 x 1080 p with 60 Hz
- Supported transmission modes: RBR, HBR, HBR2
- Maximal bandwidth: 10,8 Gbps
- HBR-Version/transfer mode: HBR1 (2,70 Gbit/s per lane)
- HDCP-Version: HDCP 1.3
- Assortment: DisplayPort Cables
- AWG: 32

- Color cable: white
- Color connector: white
- Connector 1: Mini DP, plug
- Connector 2: DP, plug
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.1a
- Ferrite filter: none
- HDTV Standard: Full HD
- Hoods: molded
- Interlock: Snap fastener
- Packaging: Polybag
- Wire material: CU
- Length: 2 m
- AOC - Active Optical Cable: no
- Shielding: Double shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	60	5.40	50.00	32.00	22.00	35,200.00
Packaging Unit Inside	1	0.09	22.00	16.00	1.50	528.00
Packaging Unit Single	1	0.09	17.00	14.00	3.00	714.00
Net single without Packaging	1	0.09	0.00	0.00	0.00	0.00

More images:

