

DIGITUS DisplayPort Connection Cable

AK-340102-010-W
EAN 4016032291428



DisplayPort connection cable, mini DP - DP M/M, 1.0m, w/interlock, DP 1.1a conform, wh

This high performance HD digital audio and video cable suits for connection of a MacBook, MacBook Air, MacBook Pro, iMac, Mac mini and Mac Pro to a Monitor, Beamer, LCD/TFT Monitor with DP interface, for example.

Ideal to connect mobile devices with displays

- Support 1080p with 30Hz
- Max. supported Video Resolution: 1920 x 1080 p with 60 Hz
- Supported transmission modes: RBR, HBR, HBR2
- Maximal bandwidth: 10,8 Gbps
- HBR-Version/transfer mode: HBR1 (2,70 Gbit/s per lane)
- HDCP-Version: HDCP 1.3
- Assortment: DisplayPort Cables
- AWG: 32

- Color cable: white
- Color connector: white
- Connector 1: Mini DP, plug
- Connector 2: DP, plug
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.1a
- Ferrite filter: none
- HDTV Standard: Full HD
- Hoods: molded
- Interlock: Snap fastener
- Packaging: Polybag
- Wire material: CU
- Length: 1 m
- AOC - Active Optical Cable: no
- Shielding: Double shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	120	5.50	50.00	31.00	22.00	34,100.00
Packaging Unit Inside	10	0.46	26.00	6.00	21.00	3,276.00
Packaging Unit Single	1	0.05	11.00	1.00	12.00	132.00
Net single without Packaging	1	0.05	1.50	15.00	23.00	0.00

More images:

