


# DIGITUS USB 3.0 connection cable

AK-300117-005-S  
EAN 4016032325581



**USB 3.0 connection cable, USB A - Micro USB B M/M, 0.5m, USB 3.0 conform, bl**

USB 3.0 connection cable, USB A - Micro USB B,M/M, 0.5m, USB 3.0 conform, bl

**The dense screening allows a reliable and fast connection of external USB 3.0 devices with the PC, also about longer distances.**

## Attributes




- Assortment: USB Cables

- AWG: 28
- Color cable: black
- Color connector: black
- Connector 1: USB A, plug
- Connector 2: Micro USB B, plug
- Ferrite filter: none
- Hoods: molded
- Wire material: CU
- Length: 0.5 m
- Shielding: triple shielding

## Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	100	4.10	38.00	30.20	31.10	35,690.40
Packaging Unit Inside	10	0.41	16.00	22.00	5.00	1,760.00
Packaging Unit Single	1	0.04	12.00	1.50	21.00	378.00
Net single without Packaging	1	0.04	12.00	1.50	21.00	0.00

## More images:





### Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable.
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schöffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)