

# DIGITUS USB Type-C connection cable, Type-C to A

AK-300136-018-S  
EAN 4016032368755



## USB Type-C connection cable, type C to A M/M, 1.8m, 3A, 480MB, 2.0 Version, bl

For connection of external USB devices (with C socket, e. g. Tablet, Notebook or Smartphone) to the USB Host (e. g. PC or Notebook). Datatransferrate up to 480 Mbps (High-Speed).

### For superfast synchronising and charging

- High speed USB data transfer rate up to 480 Mbps
- Supports up to 3A Power supply
- Support of USB PD (Power Delivery) specification
- Type-C connector can be used in both directions
- 56k pull-up resistor


### Attributes

- Assortment: USB Cables
- AWG: 30/22
- Color cable: black
- Color connector: black
- Connector 1: USB C, plug
- Connector 2: USB A, plug
- Connector surface: nickel-plated
- Ferrite filter: none
- Hoods: molded
- USB compliance: USB 2.0
- Wire material: CU
- Length: 1.8 m
- Shielding: Double shielding
- USB-C Products: yes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	200	8.10	50.00	32.00	21.00	33,600.00
Packaging Unit Inside	10	0.41	30.00	20.00	5.50	3,300.00
Packaging Unit Single	1	0.04	9.00	9.00	1.50	121.50
Net single without Packaging	1	0.04	9.00	9.00	1.50	0.00

### More images:





### Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schöffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)