

1

DIGITUS USB Type-C Connection Cable

DB-300138-010-S EAN 4016032383819





USB Type-C connection cable, type C to C M/M, 1.0m, 5V/3A 15W, 480MB, 2.0, bl

For connection of external USB devices (with C socket, e. g. PC, Tablet or Smartphone) to the USB Host (e. g. PC, Notebook). Datatransferrate up to 480 Mbps (High-Speed).

For superfast synchronising and charging

- High speed USB data transfer rate up to 480 Mbps
- Supports up to 5V/3A 15W, 480Mbps Power supply
- Support of USB PD (Power Delivery) specification
- Type-C connector can be used in both directions

Attributes


- Assortment: USB Cables
- AWG: 24/28
- Color cable: black
- Color connector: blackConnector 1: USB C, plug
- Connector 2: USB C, plug
- Connector surface: nickel-plated
- Hoods: molded
- Wire material: CU
- Length: 1 m
- Shielding: Double shielding
- USB-C Products: yes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	100	13.13	18.00	24.00	31.00	13,392.00
Packaging Unit Inside	50	6.56	16.00	11.00	29.00	5,104.00
Packaging Unit Single	1	0.13	3.00	5.50	10.00	165.00
Net single without Packaging	1	0.10	9.00	9.00	0.60	0.00

More images:







Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com