

# DIGITUS CAT 5e U/UTP twisted pair patch cord, raw

**DK-1511-P-305-1**  
**EAN 4016032425908**



**CAT 5e U-UTP patch cable, raw 305 m, paper box, AWG 26/7, PVC, sx, grey**

The raw patch cords are manufactured and tested acc. to the ISO/IEC 11801 and DIN EN 50173 specifications. They will guarantee that the installed cabling system is compliant with the ISO & EN channel specification requirements and therefore provide optimum performance levels for your cabling. The raw patch cords are suitable for the direct assembly of RJ45 connector in order to produce patch cords.

**Future-oriented standards and high-end quality for your network.**

- Insulation: HD-PE
- Outer sheath diameter: 0.55 mm nominal
- Overall diameter: 4.6 mm nominal
- Tensile loading: 150 N max.
- Dynamic bending radius: 8x AD mm min.
- Static bending radius: 4x AD mm min.
- Shipping- and storage temperature range: -10 °C up to +75 °C
- Operating temperature range: -10 °C up to +60 °C
- Installation temperature range: 0 °C up to +50 °C
- DC loop resistance: ≤ 280 Ω km
- Resistance unbalance ≤ 2%
- Insulation resistance: ≥ 2000MΩ/km @500V
- Capacitance: nom. 48 nF/km @ 800 Hz

- Capacitance unbalance (pair-ground): ≤ 1500 nF/km
- Characteristic Impedance: 100 ± 15 Ohm @ 10-100 MHz
- NVP: 67%
- Propagation delay: nom. ≤ 555 ns/100 m
- Test voltage (DC 1 min) core/core: 1000V
- Coupling attenuation: ≥ 40 dB
- Mean impedance: 100±10 Ohm @ 10-100 MHz
- Capacitance: 48 pF/m nominal @ 800 Hz
- Capacitance unbalance (pair-ground): 1.5 pF/m max. @ 1 KHz
- Insulation resistance: 2 GOhm x km min.
- DC loop resistance: 147 Ohm/Km max. (2% max. resistance unbalance)
- Voltage resistance: 72 Vdc max.
- Coupling attenuation: 40 dB
- Signal propagation delay: 450 nS/100 m max.
- Propagation delay: 20 nS/100 m max.
- Assortment: Twisted Pair Patch Cables
- Category: CAT 5e
- Shielding: U-UTP, unshielded
- Length: 305 m
- Color: grey
- Jacket: PVC
- Slim Version: no
- Structure: 4 x 2 AWG 26/7, twisted pair
- Structure: 4 x 2 AWG 26/7, twisted pair

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	2	15.30	38.50	35.00	35.00	47,162.50
Packaging Unit Inside	1	7.65	33.00	33.00	18.00	19,602.00
Packaging Unit Single	1	7.65	33.00	33.00	18.00	19,602.00
Net single without Packaging	1	6.40	30,500.00	4.60	4.60	0.00