

DIGITUS 24 Port Gigabit Ethernet PoE+ Injector, 802.3af/at, 370 W

DN-95117
EAN 4016032430384



Gigabit Ethernet PoE+ Injector Hub, 802.3at, 10G 24-port, Power Pins:3/6(+), 1/2(-), 370W

The DIGITUS® DN-95117 is an 24 port gigabit PoE+ mid-span hub (PoE injector). It offers 24 input ports for data and 24 output ports which make data and PoE available. Each PoE-port supports connected devices in accordance with the IEEE802.3af and IEEE802.3at PoE standard with 15.4 watts and/or 30 watts, such as PoE access points, PoE IP-telephones or PoE IP cameras, for example. The switch makes available a maximum budget of 370 watts for all ports and maximum budget of 30 watts per port.

Minimization of the cabling costs for PoE-capable devices

- 48 x 10/100/1000Mbps/2.5/10G (24 x input data, 24 x output data+PoE)
- Compatible with the IEEE802.3af and IEEE802.3at standards
- PoE power supply via PIN 1.2(V-) and PIN 3.6(V+)
- Maximum total output of 370 watts
- Compatible with IEEE802.3, IEEE802.3u and IEEE802.3ab standards
- Automatic cable recognition - Auto-MDI-/ MDI-X function

- Auto recognition of full and half duplex
- Power supply: 100V AC ~ 240V AC
- Operating temperature range: -10 °C to +45 °C
- Storage temperature: -20°C - 70°C
- Dimensions (mm): 440(L) x 345(W) x 45(H)
- MTBF: 100,000 hours
- Power consumption: 20W
- Number of ports: 24
- PoE Power budget: 370 W
- PoE standard: IEEE802.3af (PoE)
- Ethernet speed: Gigabit
- Industrial usage: no

Package contents

- 24 port gigabit PoE+ injector
- Quick start guide
- Power Cord cable
- Mounting accessories

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	3	16.00	52.50	33.00	44.00	76,230.00
Packaging Unit Inside	1	5.33	50.50	40.50	9.50	19,429.90
Packaging Unit Single	1	5.33	50.50	40.50	9.50	19,429.90
Net single without Packaging	1	4.39	44.00	34.50	4.50	0.00

More images:

