

# DIGITUS Displayport connection cable, DP, w/ amp.

**AK-340105-200-S**  
**EAN 4016032433743**



## Displayport Connection Cable, Type DP, w/ amp. M/M, 20.0m, w/lock, UHD 4K, DP 1.2, gold, bl

This high performance HD digital audio and video cable for example is used to connect a PC or notebook with DisplayPort interface to a monitor with DisplayPort interface.

### A/V connection over long distances without signal loss

- Supports video format: 4K/2K@24Hz, 4K/2K@30Hz or 4K/2K@60Hz
- Supported video resolution: 4K (3840x2160)@60Hz and Full HD (1920x1080)@120Hz
- No external power supply required
- Secure and reliable connection thanks to the plug lock
- Integrated, active signal amplifier
- Supported transmission modes: RBR, HBR, HBR2
- Maximum bandwidth: 21.6 Gbps
- HBR version/transfer mode: HBR2 (5.40 Gbit/s per lane)
- HDCP version: HDCP 1.3

### Attributes

- Assortment: DisplayPort Cables
- AWG: 28
- Color cable: black
- Color connector: black
- Connector 1: DP, plug
- Connector 2: DP, plug
- Connector surface: gold-plated
- DisplayPort standard: DisplayPort 1.2
- HDTV Standard: Ultra HD 4K
- Hoods: plastic
- Interlock: Snap fastener
- Wire material: CU
- Length: 20 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

### Logistics

	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	6	11.50	38.10	31.10	30.20	35,784.30
Packaging Unit Inside	1	1.92	0.00	0.00	0.00	0.00
Packaging Unit Single	1	1.92	33.50	33.50	8.00	8,978.00
Net single without Packaging	1	1.79	25.00	24.00	8.00	0.00

### More images:



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schöffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)