

# DIGITUS Universal Travel Docking Station, USB Type-C™

DA-70865  
EAN 4016032441250



### Universal Travel Docking Station, USB-C, 9-Port 2x video, 2x USB-C, 2x USB3.0, RJ45, 2x card reader

With the USB Type-C™ Universal Travel Docking Station from DIGITUS®, you always have the most important interfaces with you. The docking station extends your notebook by nine additional ports. It offers two video interfaces (HDMI and VGA). The highest possible supported resolution (HDMI): Brilliant UHD (4K2K/30Hz). In addition, it offers two USB 3.0 ports, one promises a charging function for mobile devices (BC 1.2) as well. Likewise, it offers two USB-C™ ports - 1x data transfer, 1x Power Delivery (PD 3.0). Your notebook can also be connected to the network by cable via the Gigabit Ethernet port. The whole thing is rounded off by two card readers (MicroSD, SDHC, SDXC / MMC). Due to the compact size, the low weight as well as the stowable connecting cable, the docking station is the perfect companion when out and about and when travelling.

### The most important interfaces are always there – expands your notebook by 9 additional ports via one single USB-C™ port

- Supports Ultra HD (30Hz), 3840 x 2160p resolution (HDMI)
- 1 x HDMI (UHD resolution, 4K/30 Hz)
- 1 x VGA (Full HD 1080p / 60 Hz)
- 2 x USB 3.0 port for super-speed data transfer and one with additional charging function (BC 1.2) for mobile devices
- 1 x USB-C™ for data transfer (5 Gbit/s max.)
- 1 x USB-C™ with Power Delivery (PD) 3.0 functionality (100W, 20V/5A)
- 1 x Gigabit Ethernet port – connection of your notebook to the network by cable (10/100/1000 Mb/s)
- 2 x Card readers (MicroSD / SDHC, SDXC, MMC)
- Stowable USB-C™ connecting cable (10 cm) – the connecting cable can be stored in the casing
- USB-C™ version: USB 3.1 (Gen 1)
- Ultra-compact size as well as low weight – perfect for travelling and out and about

- Color: black
- Dimensions: L 12.2 x W 7.0 x H 1.4 cm
- Weight: 90 g
- Not all USB-C™ ports support all features of the USB Type-C™ standard. Make sure your notebook's USB-C™ port supports DisplayPort Alternate Mode (DP-Alt Modi) and USB Power Delivery (PD).
- The video output capability depends on the graphic card of your notebook and the connected monitor. Certain graphics cards have limited MST support, while some monitors also limit the available resolution.
- The used power supply must supply at least 60 watts to power a connected notebook as well as the docking station via the USB-C™ port
- The used power supply must supply at least 60 watts to power a connected notebook as well as the docking station via the USB-C™ port
- HDTV Resolution max.: 3840 x 2160 Pixel, 30Hz
- Housing: Plastic
- LAN connector (RJ45): yes
- USB-C Power Delivery: 100W
- Card reader: yes
- Number of audio ports: 0
- Number of display ports: 1
- Number of network ports: 1
- Number of USB A ports: 2
- Number of USB-C ports: 2
- Number of video ports: 2
- USB-C Products: yes
- Video connection ports: HDMI, VGA

### Package contents

- Universal Travel Docking Station, USB Type-C™
- User manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	40	9.04	33.00	30.00	37.00	36,630.00
Packaging Unit Inside	1	0.23	14.00	17.00	2.50	595.00
Packaging Unit Single	1	0.23	14.00	17.00	2.50	595.00
Net single without Packaging	1	0.09	12.20	7.00	1.40	0.00

More images:

