

# **DIGITUS HDMI Premium High Speed with Ethernet Connection Cable**

DK-330123-020-S EAN 4016032448747





# HDMI Premium High Speed connection cable, type A M/M, 2.0m, w/Ethernet, Ultra HD 60p, gold, bl

This HD and 3D suitable cable used for connection of audio/video devices, such as Blu-ray player, game pads or consoles, etc., for example, with a TV, monitor or computer. Also capable for use of any IP-based application.

### 4K/Ultra HD and HDR capable + Ethernet connectivity

- Support of HDMI 2.0 Features
- Supports Ultra HD (60Hz) up to 3840 x 2160p resolution
- Support 4K 3D
- Support of High Dynamic Range (HDR)
- Support Audio Return Channel (ARC)
- Support Consumer Electronic Control (CEC)
- Support Lip-Sync (audio/video synchronisation)
- Dolby TrueHD capable

- Multi Stream audio/video support
- 21:9 Cinemascope support
- 32 Channel Audio support
- · With Ethernet Channel (HEC)

#### **Attributes**

- Color cable: black
- Connector 1: HDMI type A, plug
- Connector 2: HDMI type A, plug
- Connector surface: gold-plated
- HDMI Standard: Premium High Speed HDMI with Ethernet
- HDTV Resolution max.: 3840 x 2160 Pixel, 60Hz
- HDTV Standard: Ultra HD 4K
- Length: 2 m
- AOC Active Optical Cable: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	50	12.50	46.00	30.00	25.00	34,500.00
Packaging Unit Inside	10	2.50	35.60	55.90	12.50	24,875.50
Packaging Unit Single	1	0.25	18.70	29.90	2.50	1,397.82
Net single without Packaging	1	0.17	15.00	15.00	2.50	0.00

## More images:











#### Safety notes

- $\bullet \quad \text{When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.}\\$
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- · Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

#### EU responsible person

 $\ensuremath{\mathsf{EU}}$  based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com