

DIGITUS USB Type-C adapter / converter cable, Type-C to DVI

AK-300332-020-S EAN 4016032451358





USB Type-C adapter cable, Type-C to DVI M/M, 2.0m, 1080p@60Hz, bl, gold

The USB Type-C to DVI adapter / converter cable allows a direct connection of monitor or projector to a USB-C device. The adapter / converter cable is a must-have accessory, whether you connect your Notesbook privately to a monitor or professionally for presentations via an DVI projector.

Connect your USB-C device directly to a monitor, TV or beamer - No need of an additional Adapter.

- Your USB-C equipped device must support video (DP alt mode) to work with this adapter / converter cable.
- Video output capability depends on the graphics card of your notebook and the connected monitor. Some screens also limit the available resolution.

- Support Full HD 1080p@60Hz
- Resolution up to 2560 x 1600 (WQXGA)

Attributes

- AWG: 26
- Color cable: black
- Connector 1: USB C, plug
- Connector 2: DVI-D (24+1), plug
 Connector surface: nickel-plated
- · Ferrite filter: none
- Length: 2 m
- · Shielding: Double shielding
- USB-C Products: yes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	40	5.88	35.00	26.00	24.00	21,840.00
Packaging Unit Inside	10	1.47	30.00	8.00	25.00	6,000.00
Packaging Unit Single	1	0.15	17.00	3.00	13.00	663.00
Net single without Packaging	1	0.12	15.00	3.00	14.00	0.00

More images:

















Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum
 operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com