

DIGITUS USB 2.0 charger cable set, type A - micro B

AK-870900-010-S
EAN 4016032455356



3x



USB 2.0 data/charger cable set, USB A to micro B M/M, 1.0m, 3er Set, 3A, Version 2.0, bl

For connection of external USB devices (with USB micro B socket, e.g. MP3 -player, smart phone or external HDD enclosure) to the USB host (e. g. PC, notebook or USB hub). Data transfer rate up to 480 Mbps (High-Speed).

With 3 cables in one package, you have the perfect backup cable for everyday use, whether in the office, at home or in the car.

- High-Speed data transfer rates of up to 480 Mbps
- Power supply up to 5V/0,5A and 2.5W

- Copper wire, foil and braid shielding for robustness and reliable connection



Attributes

- AWG: 28
- Color cable: black
- Connector 1: USB A, plug
- Connector 2: Micro USB B, plug
- Connector surface: nickel-plated
- Ferrite filter: none
- USB compliance: USB 2.0
- Length: 1 m
- Shielding: Unshielded

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	150	13.00	22.00	32.00	42.00	29,568.00
Packaging Unit Inside	10	0.87	34.00	28.00	9.00	8,568.00
Packaging Unit Single	1	0.09	27.00	19.00	0.90	461.70
Net single without Packaging	1	0.08	13.00	13.00	0.80	0.00

More images:





Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schöffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com