

DIGITUS 2.5" SSD/HDD enclosure, SATA 3, USB 3.0 Type-C™

DA-71113-1
EAN 4016032461401



SSD/HDD SATA Enclosure, 2.5" USB Type-C for SATA III 2.5"

The external DIGITUS® SSD/HDD hard disk enclosure enables you to use your SSD/HDD in a modern and stylish enclosure. You can easily insert the hard disk into the enclosure without any additional tools and connect the enclosure to your PC or laptop using the integrated USB-C™ cable. The ease of use enables quick installation of a 2.5" SATA I-III SSD/HDD hard disk (9.5/7 mm). The USB 3.0 interface guarantees high data transfer rates of up to 5 Gbps. The slim and stylish aluminium enclosure enables comfortable transfer and quick retrieval of your data at all times. No additional power adaptor is required, power is supplied via the USB Type-C™ port.

SATA hard disks can be inserted into the external 2.5" SSD/HDD enclosure without tools. High data transfer rates of up to 5 Gbps are possible thanks to USB 3.0 with SuperSpeed.

- Supports SATA I-III SSDs/HDDs with a mounting height of 7 to 9.5 mm
- Supported capacity: up to 2 TB
- Screwless design - no additional tools required
- USB 3.0 (Gen. 1) SuperSpeed - data transfer rate up to max. 5 Gbps
- SATA III - data transfer rate up to max. 5 Gbps

- Chipset: JMS578
- LED activity indicator
- Stylish and high-quality aluminium enclosure
- Supports hot plugging and is plug-and-play capable
- Power supply via the USB port
- Supports: Win 10, 8, 7, macOS 9.x or higher, Linux 2.4.x or higher, Google Chrome OS
- Operation temperature: 5 to 50 °C
- Storage temperature: -40 to 70 °C
- Operating humidity: 5 to 90% (non-condensing)
- Dimensions: L 13.2 x W 7.8 x H 1.6 cm
- Weight: 90 g
- Color: Gray

Attributes

- USB-C Products: yes

Package contents

- 2.5" SSD/HDD enclosure, SATA 3, USB 3.0 Type-C™
- with integrated USB-C™ connection cable
- User Manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	40	10.00	43.50	37.50	28.50	46,490.60
Packaging Unit Inside	1	0.25	17.60	13.00	4.00	915.20
Packaging Unit Single	1	0.25	13.22	7.80	1.60	164.99
Net single without Packaging	1	0.09	13.20	7.80	1.60	0.00

More images:



EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schöffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com