

# DIGITUS 3-in-1 charging cable

AK-300160-010-S  
EAN 4016032467113



## USB charger cable, 1m 3 in 1 cable, nylon braid, black

The DIGITUS® 3-in-1 charging cable is ideal for charging your portable devices on a power supply, PC or other device with a USB-A port. Use a single cable to charge all your devices. Its compact dimensions make this cable an ideal companion for home, office or travel.

### 3-in-1 multi-charging cable for connecting devices with a USB-C, micro-USB or 8-pin connector to a USB-A port

- Supported charging power: 10 W (5 V / 2 A)
- Operating temperature: -10 °C to +50 °C
- Operating humidity: 0 - 75%

## Attributes

- AWG: 30
- Color cable: black
- Connector 1: USB A, plug
- Connector 2: USB C, plug
- Connector surface: nickel-plated
- Wire material: CU
- Length: 1 m
- USB-C Products: yes

## Logistics

|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³       |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------|
| Packaging Unit Carton        | 150          | 13.00       | 44.00      | 33.00      | 22.00       | 31,944.00 |
| Packaging Unit Inside        | 5            | 0.43        | 19.00      | 15.00      | 3.00        | 855.00    |
| Packaging Unit Single        | 1            | 0.09        | 18.00      | 8.00       | 2.00        | 288.00    |
| Net single without Packaging | 1            | 0.08        | 3.00       | 14.00      | 13.00       | 0.00      |

## More images:





#### Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

#### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schöffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)