

DIGITUS HP-compatible SFP+ 10G SM 1310nm 10Km with DDM

DN-81201-01
EAN 4016032370031



10G SFP+ Module, Singlemode, DDM, HP-compatible LC Duplex Connector, 1310nm, up to 10km, HP

De DIGITUS® Mini GBIC (SFP) zendontvanger module biedt de hoogste kwaliteit en betrouwbaarheid. Of het nu gaat van switch naar switch, van converter naar switch, van converter naar converter of van andere, uitgebreide toepassingen: De grote verscheidenheid aan DIGITUS®-modules stelt u in staat om flexibel gebruik te maken van de glasvezeltechnologie. Dankzij de conformiteit met de MSA-norm (Multi Source Agreement) is een compatibiliteit met externe fabrikanten gegarandeerd.

De plug-and-play glasvezelaansluiting

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Ondersteunt DDM (Digital Diagnostic Monitoring)
- Hoge kwaliteit en de beste bescherming tegen uitval
- 10 Gbps Maximum Data Rate
- Compliant to IEEE802.3ae 10 Gigabit Standard
- Klasse 1 laserproduct volgens EN 60825-1
- Eenvoudige Plug and Play-installatie
- Compatibel met MSA (Multi Source Agreement)

- Hot pluggable
- Aansluiting: 1x LC duplex
- Golflengte: 1310 nm
- Overdrachtvermogen: Minimum -8 dBm, Maximum -0,5 dBm
- Gevoeligheid van Ontvangstvermogen: Minimum -12,5 dBm
- Voor afstanden van tot op 10,0km
- Veilig snelvergrendelingsmechanisme
- Bedrijfstemperatuur: 0°C~70°C
- Modus: Enkele modus
- Connector: LC
- Distance Unit: 10
- Golflengte: 1310 nm
- DDM ondersteuning: yes
- Broadcasting Mode: Unidirectioneel
- Compatibiliteit met fabrikant: HP
- Ethernetsnelheid: 10 Gigabit

Package contents

- SFP-module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	20	2.00	41.00	26.00	16.00	17,056.00
Packaging Unit Inside	1	0.10	3.00	11.50	9.00	310.50
Packaging Unit Single	1	0.10	3.00	11.50	9.00	310.50
Net single without Packaging	1	0.03	5.50	1.20	0.80	0.00

More images:



SFP Modules							
Part Number	SKU Code	Speed	Distance	Connector	Mounting	Operating Temperature	Substitutable Module
DA-PA01	4010000000001	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA02	4010000000002	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA03	4010000000003	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA04	4010000000004	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA05	4010000000005	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA06	4010000000006	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA07	4010000000007	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA08	4010000000008	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA09	4010000000009	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA10	4010000000010	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA11	4010000000011	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA12	4010000000012	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA13	4010000000013	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA14	4010000000014	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA15	4010000000015	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA16	4010000000016	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA17	4010000000017	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA18	4010000000018	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA19	4010000000019	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA20	4010000000020	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA21	4010000000021	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA22	4010000000022	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA23	4010000000023	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA24	4010000000024	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA25	4010000000025	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA26	4010000000026	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA27	4010000000027	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA28	4010000000028	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA29	4010000000029	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA30	4010000000030	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA31	4010000000031	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA32	4010000000032	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA33	4010000000033	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA34	4010000000034	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA35	4010000000035	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA36	4010000000036	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA37	4010000000037	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA38	4010000000038	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA39	4010000000039	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA40	4010000000040	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA41	4010000000041	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA42	4010000000042	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA43	4010000000043	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA44	4010000000044	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA45	4010000000045	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA46	4010000000046	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA47	4010000000047	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA48	4010000000048	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA49	4010000000049	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	
DA-PA50	4010000000050	10 Gbps	300m	LC Duplex Small Form-factor Pluggable	19mm	-40 to 85 °C	

