

DIGITUS 4K HDMI® Matrix Switch, 4x4, 19"

DS-43308
EAN 4016032467359



4x4 HDMI Matrix Switch, 19 inch 4K/60Hz, silver/black

With the 4x4 HDMI® Matrix Switch from DIGITUS®, you can choose between 4 HDMI® signal sources and output signals to 4 different HDMI® outputs independently or simultaneously. All inputs can be assigned to different outputs or all outputs as desired. Convenient operation via remote control, on the device or using the RS232 interface. A bandwidth of 18 Gbps is also supported for smooth reproduction of high-resolution 4K content as well as Full 3D. With the 19" mounting brackets included in delivery, this matrix switch can be installed in 19" racks, server cabinets or wall cabinets.

Distribute up to four different HDMI® signals on up to four HDMI® displays independently of one another with UHD resolutions up to 4K

- Resolution: 4K / 60 Hz
- Bandwidth: 18 Gbps (600 MHz)
- Supports 3D applications in Full HD
- Color depth: 24 bit
- Subsampling: YUV: 4:4:4
- Display Data Channel (DCC): DDC 2B
- HDMI® version: 2.0
- HDCP version: 2.0
- Additional resolutions:
 480i@60Hz, 480p@60Hz, 576i@50Hz, 576p@50Hz, 720p@50/60Hz, 1080i@50/60Hz, 1080p@50/60Hz, 4Kx2K@30/60Hz
- Supports audio formats: DTS-HD/Dolby-true HD/LPCM7.1/DTS/Dolby-AC3/DSD

- RS232 interface: 3-pin terminal
- Can be installed in 19" racks/cabinets, 1U
- Power supply power adapter: 100 - 240 VAC, 50/60 Hz
- Power supply device: 12 V / 2 A (24 W)
- Current consumption device: 20 W max.
- Cable length power adapter: ca. 1.5 m
- Operating temperature: 0°C ~ 60°C
- Storage temperature: -20 °C to +60 °C
- Operating humidity: 0% - 90% RH (non-condensing)
- Case material: Metal
- Dimensions: W 43 x D 17.1 x H 2.8 cm
- Weight: 1.65 kg
- Color: Black / silver
- HDTV resolutie max.: 3840 x 2160 pixels, 60 Hz
- Aantal ingangspoorten: 4
- Aantal uitgangspoorten: 4
- Signaalingang: HDMI
- Signaaluitgang: HDMI
- Video aansluitpoorten: HDMI

Package contents

- 1 x 4K HDMI® Matrix Switch, 4x4, 19"
- 1 x 4K HDMI® Matrix Switch, 4x4, 19"
- 1 x Power adapter 12 V / 2 A
- 1 x Remote control
- 2 x Brackets for 19" rack mount
- 1 x User manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	5	13.68	49.00	55.00	32.50	87,587.50
Packaging Unit Inside	1	2.74	0.00	0.00	0.00	0.00
Packaging Unit Single	1	2.74	27.00	48.80	10.70	14,098.30
Net single without Packaging	1	1.65	17.10	43.00	2.80	0.00

More images:

