

DIGITUS Universal Charging Adapter, USB-C™, 20 W

DA-10196
EAN 4016032474036



USB-C Wall Charger 20W, PD 3.0, white

The Universal Charging Adapter from DIGITUS® is suitable for USB-C™ devices such as smartphones, tablets or notebooks and provides an output of up to 20 W. The integrated short circuit, surge and excess current protection provides added security. Furthermore, the integrated excess heat protection prevents potential overloads and damages to the charger or connected devices. The LED display provides information about the current charging status. Its compact dimensions make the charging adapter ideal for on the go.

High-performance charging adapter with an output of up to 20 W for USB-C™ devices of all kinds with numerous safety features

- Connection: USB Type-C™
- Compatible with smartphones with 20 W charging adapted, e.g. from Apple, Huawei, XIAOMI, Google, Samsung
- Input voltage: 100 - 240 V AC, 50/60 Hz
- Plug designation: CEE-7/16 Euro plug (Type C)
- Standby power consumption: 0.1 W
- Output voltage: 5 V / 3 A, 9 V / 2.22 A (20 W max.)

- Supports Power Delivery 3.0 with 20 W charging capacity
- Surge protection / excess current protection / overload protection / short circuit protection
- Protection against overheating with automatic switch-off and recovery (auto-recovery)
- Operating temperature: 0 °C to 40 °C
- Storage temperature: -20 °C to +85 °C
- Operating humidity: 20% - 90% RH (non-condensing)
- Storage humidity: 5% - 95% RH (non-condensing)
- Housing: Fire-resistant material
- Dimensions: L 64.1 x W 44 x H 27.7 mm
- Color: White
- Weight: 59 g
- Stijl: Lader/Voeding
- USB-C producten: yes

Package contents

- 1 x Universal Charging Adapter, USB-C™, 20 W
- 1 x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	100	8.50	37.00	67.00	19.00	47,101.00
Packaging Unit Inside	1	0.09	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.09	8.00	13.00	3.50	364.00
Net single without Packaging	1	0.05	4.10	6.20	2.50	0.00

More images:

