

DIGITUS Wall Mounting Cabinet Unique Series - 600x450 mm (WxD)

DN-19 16-U

EAN 4016032135234



16U wall mounting cabinet, Unique 820x600x450 mm, color grey (RAL 7035)

The network cabinets for wall installation from the Unique series were developed for especially convenient and flexible network cabling. There is a sliding cable inlet with foam rubber seal in the roof of each cabinet. The back wall and floor plate are equipped with pre-cut cable inlets with a plastic cover. To accommodate a fan module, the roof structure is also equipped with a pre-cut area. Two pair of galvanized 483 mm (19") profile rails labeled with rack units readable in both directions are installed on the inside. Their depth can be adjusted. Each cabinet is made of up to 1.5 mm thick sheet steel. Coloring is done with electrostatic powder coating in the standard colors gray (RAL 7035) or jet black (RAL 9005). Removable and lockable side walls in a modular design as well as lockable and removable front door improve accessibility. The door hinges can be switched. Wall installation is accomplished in two easy work steps: The housing frame plate is bolted on the wall and then connected with the housing. With optionally available levelling feet or casters, the wall housings from the Unique series can also be used as a free-standing unit.

A série DIGITUS® Unique foi fabricada, concebida e desenvolvida para corresponder aos mais elevados requisitos da infraestrutura de TI.

- Classe de proteção IP20
- Dispositivo de bloqueio de 1 ponto na porta frontal
- Os painéis laterais são bloqueáveis e amovíveis
- Calhas de perfil de 483 mm (19") no lado frontal e traseiro, montadas no armário, galvanizadas

- As calhas de perfil de 483 mm (19") podem ser ajustadas em profundidade e estão providas com marcação da unidade de altura
- Folha de aço robusta 1,1 - 1,5 com elevada capacidade de carga, pintada por pulverização
- O telhado está preparado para elemento de ventilação (entradas perfuradas)
- Ranhuras de ventilação para ventilação e saída ativa e passiva
- Vários pontos de ligação terra no armário, para componentes embutidos
- É fornecido completamente montado

Attributes

- Cabinet type: Wall mounting cabinet
- Color: light grey, RAL 7035
- Depth: 450 mm
- Front door: Glass door, single opening
- Load capacity: 100 kg
- Side panels: Both sides
- Units: 16
- Width: 600 mm
- IP protection class: IP20
- Mounted: yes

Package contents

- Earthing wire set
- Installation set (screws, cage nuts, washers)
- 2 x Keys

| Logistics | | | | | | |
|------------------------------|--------------|-------------|------------|------------|-------------|------------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 1 | 28.90 | 49.00 | 67.00 | 83.00 | 272,489.00 |
| Packaging Unit Inside | 1 | 28.90 | 49.00 | 67.00 | 83.00 | 272,489.00 |
| Packaging Unit Single | 1 | 28.90 | 49.00 | 67.00 | 83.00 | 272,489.00 |
| Net single without Packaging | 1 | 27.00 | 45.00 | 60.00 | 82.00 | 253,134.00 |

More images:



Safety notes

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be laid neatly and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com