

DIGITUS Fiber Optic Patch Cord, E2000 (8° APC) to E2000 (8° APC), Singlemode

AL-9E2000-01I EAN 4016032204725





FO patch cord, duplex, E2000 (APC) to E2000 (APC) R+M, SM OS2 09/125 æ, 1 m $\,$

Assmann Professional offers a wide range of high quality fiber optic patch cables. Practically every request and every requirement is covered by the broad range of cable types. The product range includes OM1, OM2, OM3 and OS2 versions. Assmann fiber optic installation cables guarantee the best performance and fail-safety. All cables are single packed a polybag with test report.

Melhor desempenho e melhor qualidade de ligação com a rede.

LSOH

Attributes

• Assortment: Fiber Optic Patch Cables

· Boot: single-color

Cable type: I-VH 2E9/125µ

Color cable: yellow

· Connector 1: E2000 (APC)

Connector 2: E2000 (APC)

Fiber class: OS2

• Fiber diameter: 9/125µ

Mode: Singlemode

Packaging: Polybag

• Length: 1 m

| Logistics | | | | | | |
|------------------------------|-----------------|----------------|---------------|---------------|----------------|-----------|
| | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm³ |
| Packaging Unit Carton | 30 | 2.20 | 30.00 | 30.00 | 30.00 | 27,000.00 |
| Packaging Unit Inside | 1 | 0.07 | 0.00 | 0.00 | 0.00 | 0.00 |
| Packaging Unit Single | 1 | 0.07 | 20.00 | 19.00 | 1.00 | 380.00 |
| Net single without Packaging | 1 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- · eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect
 against harmful radiation.
- · When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal
 quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum
 operating temperature of the cable
- · Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.



EU responsible person

EU based economic operator ensuring the product complies with the required regulations. ASSMANN Electronic GmbH Auf dem Schüffel 3 $\,$

Lüdenscheid, Germany https://www.assmann.com info@assmann.com