

DIGITUS Wall Mounting Cabinet Unique Series - 600x450 mm (WxD)

DN-19 07-U-SW
EAN 4016032257639



7U wall mounting cabinet, Unique 420x600x450 mm, color black (RAL 9005)

The Wall Mounting Cabinets of the Unique Series were designed for the user friendly installation of active- and passive network components accompanied by a neat cable management. Each rack consists of up to 1.5 mm strong steel sheet material which ensures a very good stability as a robust steel construction. The color is created by powder coating in grey (RAL 7035) and black (RAL 9005). Wall installation can be done easily, there are two steps: Mount the rear wall of the housing on your wall and then simply connect it with the housing. Separately leveling feet or castors are available for free standing purposes. Door and side panels are easy to detach and the door stop can be changed from right to left. The roof contains air ventilation slots for a better air circulation. Each wall mounting cabinet contains one pair (two pieces) of mounted 483 mm (19") profile rails inside (wall mounting cabinets from 600 mm depth contain two pairs). They are galvanized, with height unit marking (countable from both directions) and variable in depth. An important aspect for each installation is the cable management. The roof of each cabinet is equipped with a sliding cable entry panel with rubber sealing. Punched out cable entries with plastic cover are present on the rear wall and base. An extensive portfolio of accessories for cable management, shelves, etc. will help to meet many requirements in daily use.

A série DIGITUS® Unique foi fabricada, concebida e desenvolvida para corresponder aos mais elevados requisitos da infraestrutura de TI.

- Classe de proteção IP20

- Dispositivo de bloqueio de 1 ponto na porta frontal
- Os painéis laterais são bloqueáveis e amovíveis
- Calhas de perfil de 483 mm (19") montadas no lado frontal, dentro do armário, galvanizadas
- As calhas de perfil de 483 mm (19") podem ser ajustadas em profundidade e estão providas com marcação da unidade de altura
- Folha de aço robusta 1,1 - 1,5 com elevada capacidade de carga, pintada por pulverização
- O telhado está preparado para elemento de ventilação (entradas perfuradas)
- Ranhuras de ventilação para ventilação e saída ativa e passiva
- Vários pontos de ligação terra no armário, para componentes embutidos
- É fornecido completamente montado
- IP protection class: IP20
- Color: black, RAL 9005
- Depth: 450 mm
- Front door: Glass door, single opening
- Units: 7
- Units: 7
- Load capacity: 100 kg
- Mounted: yes
- Side panels: Both sides
- Cabinet type: Wall mounting cabinet
- Width: 600 mm

Package contents

- Earthing wire set
- Installation set (screws, cage nuts, washers)

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	18.00	50.00	65.00	47.00	152,750.00
Packaging Unit Inside	1	18.00	50.00	65.00	47.00	152,750.00
Packaging Unit Single	1	18.00	50.00	65.00	47.00	152,750.00
Net single without Packaging	1	17.00	45.00	60.00	42.00	147,200.00

More images:

