

# DIGITUS Cabo adaptador DisplayPort

**AK-340401-001-S**  
**EAN 4016032289265**



**DisplayPort adapter cable, DP - DVI (24+5) M/F, 0.15m,w/interlock, DP 1.1 compatible, CE, bl**

Este cabo HD digital, é adequado, por exemplo, para a ligação de um computador portátil ou de um computador pessoal com uma interface DP a um monitor DVI, projector, monitor LCD-TFT através de um cabo DVI.

**Perfeito para reproduções de vídeo, jogos ou ampliação do posto de trabalho**

- Suporta até 1080p com 60 Hz
- Suporta Full HD digital, bem como uma taxa de transferência mais elevada através de Dual Link.
- Fios de cobre, blindado com película e entrançado para uma robustez e uma ligação fiável
- Plug & Play, não é necessário um controlador adicional
- Assortment: DisplayPort Cables

- AWG: 28
- Color cable: black
- Color connector: black
- Connector 1: DP, plug
- Connector 2: DVI-I, (24+5), jack
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.1a
- Ferrite filter: none
- HDTV Standard: Full HD
- Hoods: molded
- Interlock: Snap fastener
- Packaging: Polybag
- Wire material: CU
- Length: 0.15 m
- AOC - Active Optical Cable: no
- Shielding: Double shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	200	9.70	38.10	30.20	31.10	35,784.30
Packaging Unit Inside	10	0.49	40.60	40.60	8.10	13,351.70
Packaging Unit Single	1	0.05	20.00	15.00	1.62	486.00
Net single without Packaging	1	0.04	24.50	4.50	1.50	0.00

**More images:**





**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)