

DIGITUS Internal power supply cable for CPU cooler

AK-430302-002-M
EAN 4016032325185



Internal power supply cable 0.30m, IDE - IDE + 3pin cooler connector

Adaptor for connecting CPU fans with 3-pin connectors directly with a ATX/AT power supply. Particularly suitable for PCs with AT mainboards that have no direct connector for a CPU fan.

Ligação e alimentação seguras

- 3-pin CPU fan, plug <=> 1 x 5.25", plug and 1 x 5.25", jack

Attributes

- Assortment: Internal Power Supply Cables
- AWG: 22
- Color cable: various
- Color connector: transparent
- Connector 1: IDE (5,25") power plug
- Connector 2: IDE (5,25") power jack + 3-pin cooler plug
- Hoods: plastic
- Wire material: CU
- Length: 0.3 m
- Shielding: Unshielded

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	500	7.26	38.50	31.00	32.00	38,192.00
Packaging Unit Inside	10	0.15	21.00	16.00	4.00	1,344.00
Packaging Unit Single	1	0.01	17.00	7.50	1.50	191.25
Net single without Packaging	1	0.02	13.00	3.50	1.00	0.00

Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com