

DIGITUS Network Rack Dynamic Basic Series - 600x800 mm (WxD)

DN-19 42U-6/8-DB
EAN 4016032336754



42U network rack, Dynamic Basic 2040x600x800 mm, color black (RAL 9005)

The network cabinets from the Dynamic series were developed for easy and especially cost-optimized network expansion. Clever placement of the cable inlets ensures effortless installation for every application. They are located at the back center in the floor structure, protected by a bolted cover plate. Cabinets from a width of 800 mm also feature cable inlets with a plastic cover to the left and right. These are also integrated into the roof (1 x for 600 mm cabinet width, 3 x for 800 mm cabinet width). To accommodate a fan module, the roof structure is also equipped with a pre-cut area. Two pairs of galvanized 483 mm (19") profile rails labeled with rack units readable in both directions are installed on the inside. Their depth is adjustable and they are connected to additional depth bars in the cabinet. Each cabinet is made of up to 1.5 mm thick sheet steel. Coloring is done with electrostatic powder coating in the standard colors gray (RAL 7035) or jet black (RAL 9005). Removable side and back walls as well as lockable and removable front door improve accessibility. The door hinges can be switched. Furthermore, the cabinets can be completely dismantled if necessary due to their collapsible design.

The DIGITUS® Dynamic Basic Series is made for high demand IT-Infrastructure Solutions - designed and developed on highest standard in Germany

- Classe de proteção IP20
- Dispositivo de bloqueio de 1 ponto na porta frontal
- inc. 4 pés de nivelamento, que já se encontram montados sob o armário
- Calhas de perfil de 483 mm (19") no lado frontal e traseiro, montadas no armário, galvanizadas

- As calhas de perfil de 483 mm (19") podem ser ajustadas em profundidade e estão providas com marcação da unidade de altura
- Chapa de aço de 1,5 mm de espessura
- Estrutura muito rígida através de uma tecnologia especial de dobragem de chapa metálica
- O telhado está preparado para elemento de ventilação (entradas perfuradas)
- Vários pontos de ligação terra no armário, para componentes embutidos
- O telhado está preparado para elemento de ventilação (entradas perfuradas)
- É fornecido completamente montado
- Cabinet type: Network cabinet
- Color: black, RAL 9005
- Depth: 800 mm
- Front door: Glass door, single opening
- Load capacity: 600 kg
- Rear door: Rear panel with lock, detachable
- Rear door: Rear panel with lock, detachable
- Side panels: Both sides
- Units: 42
- Width: 600 mm
- IP protection class: IP20
- Mounted: yes

Package contents

- Earthing wire set
- Installation set (screws, cage nuts, washers)
- 2 x keys

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	83.00	85.00	65.00	209.00	1,154,720.00
Packaging Unit Inside	1	83.00	85.00	65.00	209.00	1,154,720.00
Packaging Unit Single	1	83.00	85.00	65.00	209.00	1,154,720.00
Net single without Packaging	1	82.00	80.00	60.00	204.00	0.00

More images:

