

DIGITUS Network Rack Dynamic Basic Series - 800x800 mm (WxD)

DN-19 32U-8/8-DB
EAN 4016032350255



32U network rack, Dynamic Basic 1590x800x800 mm, color black (RAL 9005)

The Racks of the Dynamic Basic Series were designed for the user friendly installation of active- and passive network components accompanied by a neat cable management. Each rack consists of up to 1.5 mm strong steel sheet material which ensures a very good stability as a robust steel construction due to special plate curving technique. The color is created by powder coating in grey (RAL 7035) and black (RAL 9005). For certain conditions, where the set-up location is difficult to reach, the rack can be disassembled. Doors can be easily detached and the door stop can be changed from right to left. Furthermore the roof is ready for the mounting of an air ventilation unit. Each rack contains 2 pairs (4 pieces) of 483 mm (19") profile rails inside which are galvanized and with height unit marking (countable from both directions). They are variable in depth and connected with additional depth support bars to realize extensive 483 mm (19") equipment installations. An important aspect for each installation is the cable management. The base of each rack is equipped with a punched out cable entry covered with a metal plate, whereas the base of 800 mm width racks gets extended with additional punched out cable entries with plastic covers left and right. These are also placed in the roof (1x for 600 mm width cabinets, 3x for cabinets from 800 mm width. An extensive portfolio of accessories for cable management, shelves, etc. will help to meet many requirements in daily use.

The DIGITUS® Dynamic Basic Series is made for high demand IT-Infrastructure Solutions - designed and developed on highest standard in Germany

- Classe de proteção IP20
- Dispositivo de bloqueio de 1 ponto na porta frontal
- inc. 4 pés de nivelamento, que já se encontram montados sob o armário

- Calhas de perfil de 483 mm (19") no lado frontal e traseiro, montadas no armário, galvanizadas
- As calhas de perfil de 483 mm (19") podem ser ajustadas em profundidade e estão providas com marcação da unidade de altura
- Chapa de aço de 1,5 mm de espessura
- Estrutura muito rígida através de uma tecnologia especial de dobragem de chapa metálica
- O telhado está preparado para elemento de ventilação (entradas perfuradas)
- Vários pontos de ligação terra no armário, para componentes embutidos
- O telhado está preparado para elemento de ventilação (entradas perfuradas)
- É fornecido completamente montado
- IP protection class: IP20
- Color: black, RAL 9005
- Color: black, RAL 9005
- Depth: 800 mm
- Front door: Glass door, single opening
- Units: 32
- Load capacity: 600 kg
- Mounted: yes
- Rear door: Rear panel with lock, detachable
- Side panels: Both sides
- Cabinet type: Network cabinet
- Width: 800 mm

Package contents

- Earthing wire set
- Installation set (screws, cage nuts, washers)

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	74.00	85.00	85.00	171.00	1,235,480.00
Packaging Unit Inside	1	74.00	85.00	85.00	171.00	1,235,480.00
Packaging Unit Single	1	74.00	85.00	85.00	171.00	1,235,480.00
Net single without Packaging	1	73.00	80.00	80.00	159.00	0.00