

DIGITUS Server Rack Unique Series - 600x1200 mm (WxD)

DN-19 SRV-47U-6/12
EAN 4016032364351



47U server rack, Unique, 2272x600x1200 mm perforated steel doors, color grey (RAL 7035)

The Server Racks of the Unique Series were designed for the user friendly installation of active- and passive network components accompanied by a neat cable management. Each rack consists of up to 1.5 mm strong steel sheet material which ensures a very good stability as a robust steel construction due to special plate curving technique. The color is created by powder coating in grey (RAL 7035) and black (RAL 9005). All doors can be easily detached and the door stop can be changed from right to left. The roof is present with an added perforated cover for a better air circulation Furthermore the roof is ready for the mounting of an air ventilation unit. Each server rack contains 2 pairs (4 pieces) of 483 mm (19") profile rails inside which are galvanized and with height unit marking (countable from both directions). They are variable in depth and connected with additional depth support bars to realize extensive 483 mm (19") equipment installations. With a load capacity of up to 1000 kg they can cope perfectly with server applications. The side panels are horizontally divided which ensures best accessibility to the mounted equipment. An important aspect for each installation is the cable management. The top and base of each rack is equipped with a sliding cable entry panel with rubber sealing. For cabinets with 800 mm width, the possibilities of cable management get enhanced with additional cable entries with brushes left and right in the top and base chassis. An extensive portfolio of accessories for cable management, shelves, etc. will help to meet many requirements in daily use.

A série DIGITUS® Unique foi fabricada, concebida e desenvolvida para corresponder aos mais elevados requisitos da infraestrutura de TI.

- Classe de proteção IP20
- Porta traseira de duas folhas
- Porta traseira de duas folhas
- Calhas de perfil de 483 mm (19") no lado frontal e traseiro, montadas no armário, galvanizadas
- Calhas de perfil de 483 mm (19") no lado frontal e traseiro, montadas no armário, galvanizadas
- As calhas de perfil de 483 mm (19") podem ser ajustadas em profundidade e estão providas com marcação da unidade de altura
- Os suportes de profundidade embutidos proporcionam estabilidade
- Os suportes de profundidade embutidos proporcionam estabilidade
- Vários pontos de ligação terra no armário, para componentes embutidos
- Vários pontos de ligação terra no armário, para componentes embutidos
- É fornecido completamente montado
- Cabinet type: Server cabinet
- Color: light grey, RAL 7035
- Depth: 1200 mm
- Front door: Steel door, perforated, single opening
- Load capacity: 1000 kg
- Units: 47
- Width: 600 mm
- IP protection class: IP20
- Mounted: yes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	137.00	125.00	65.00	227.20	1,846,000.00
Packaging Unit Inside	1	137.00	125.00	65.00	227.20	1,846,000.00
Packaging Unit Single	1	137.00	125.00	65.00	227.20	1,846,000.00
Net single without Packaging	1	136.00	120.00	60.00	222.20	0.00

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com