

DIGITUS Extensor áudio CAT 5, até 600 m

DS-56100
EAN 4016032366997



Cat 5 Audio Extender Extension up to 600m, local + remote unit

Com o extensor áudio CAT 5 DIGITUS é possível transferir sinais áudio estéreo e de microfone até uma distância de 600 metros, utilizando apenas o extensor áudio e um cabo CAT 5. Os seus equipamentos áudio são conectados através de RCA ou de um cabo áudio de 3,5 mm e o interruptor integrado permite uma comutação simples e rápida entre as fontes ligadas.

Utilize um simples cabo de rede para aumentar o seu sinal áudio - até 600 m.

- Coloque os seus equipamentos áudio onde quer que deseje
- Aumento do sinal áudio até 600 m

- A mudança simples entre RCA e conector jack 3,5 mm via comutador é possível
- Conectores RCA dourados
- 1x saída estéreo 3,5 mm
- 1x saída RCA
- 1x RJ45
- Não necessita de uma fonte de alimentação

Package contents

- 1x Unidade áudio extensora local
- 1x Unidade áudio extensora remota
- GIR (Guia Instalação Rápida)
- Acessórios de montagem

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	40	10.50	36.00	23.50	62.00	52,452.00
Packaging Unit Inside	1	0.26	8.30	11.20	11.50	1,069.04
Packaging Unit Single	1	0.26	8.30	11.20	11.50	1,069.04
Net single without Packaging	1	0.26	7.00	10.80	2.70	0.00

More images:



Safety notes

- If the device is powered by a plug-in power supply, ensure that the power adapter is connected correctly and meets the specified requirements (e.g. voltage and current).
- Only use certified CAT5e or CAT6 cables to ensure stable signal transmission.
- For particularly long cable runs or in environments prone to interference, it is recommended to use shielded network cables.
- Make sure that all connections are tight and secure to avoid loose contacts that could affect the signal quality. Make sure that the HDMI and Ethernet connections are properly connected.
- Make sure that the CAT cable is not laid near high-voltage power lines or other strong sources of electromagnetic interference to avoid signal interference.
- Only operate the device within the specified temperature range.
- Do not use the device outdoors or in damp or wet environments
- Check all connections and cables regularly for wear or damage. Cables and connections can wear out, especially with frequent use or long installations, which can lead to poor signal quality or system failure.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com