

DIGITUS Conversor HDMI micro para VGA

DA-70460**EAN 4016032368014**

Micro HDMI to VGA converter adapter Typ D - VGA (D-Sub) connector, 3,5mm audio jack

The Digitus DA-70460 converts digital HDMI signals into analog VGA signals. Connect your devices with Micro-HDMI ports, such as tablets, Ultrabooks, or cameras, to a VGA monitor or projector and enjoy your images, videos, or presentations in large format. The converter is also equipped with a 3.5 mm audio jack. Any existing audio signal is converted in parallel. This enables additional audio playback by connecting your speakers or surround sound system.

Converte sinais HDMI micro em VGA

- Entrada: HDMI micro + 3,5 mm áudio
- Saída: VGA
- Converte sinais de vídeo e áudio de HDMI micro para VGA
- Ligue os seus dispositivos com ligação HDMI micro a monitores ou projetores VGA
- Oferece-lhe uma excelente oportunidade de ver as suas imagens, vídeos ou apresentações em grande formato
- Saída VGA compatível com todos os monitores, projetores, televisores LCD

- Compatível com muitos Ultrabooks usuais com ligação HDMI micro
- Compatível com Tablets usuais com ligação HDMI Micro (Samsung, Google, Asus etc.)
- Resolução até 1080p
- A instalação de software ou driver não é necessária
- Dimensão compacta
- Cor: Preto
- Peso: 35 g
- Dimensões: 193 x 45 x 15 mm (C x L x A)

Attributes

- HDTV Resolution max.: 1920 x 1080 Pixel, 60Hz
- HDTV Standard: Full HD
- Audio: no
- Signal input: Micro HDMI
- Signal output: VGA

Package contents

- Conversor HDMI micro para VGA

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	80	7.28	52.00	29.00	39.00	58,812.00
Packaging Unit Inside	20	1.82	27.00	25.00	17.00	11,475.00
Packaging Unit Single	1	0.09	26.50	7.50	2.30	457.13
Net single without Packaging	1	0.03	18.00	4.50	1.50	0.00

More images:**Safety notes**

- If the device is powered by a plug-in power supply, ensure that the power adapter is connected correctly and meets the specified requirements (e.g. voltage and current).
- Only use certified CAT5e or CAT6 cables to ensure stable signal transmission.
- For particularly long cable runs or in environments prone to interference, it is recommended to use shielded network cables.
- Make sure that all connections are tight and secure to avoid loose contacts that could affect the signal quality. Make sure that the HDMI and Ethernet connections are connected correctly.
- Make sure that the CAT cable is not laid near high-voltage power lines or other strong sources of electromagnetic interference to avoid signal interference.
- Only operate the device within the specified temperature range.
- Do not use the device outdoors or in damp or wet environments
- Check all connections and cables regularly for wear or damage. Cables and connections can wear out, especially with frequent use or long installations, which can lead to poor signal quality or system failure.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com